LEDPLUS ROUND SMALL
ASYMMETRIC (LED)

Project name:

Type:



Ground / wall / garden recessed luminaire. Provides an asymmetric light distribution.

Luminaire characteristics:
Power input: 0.4W (remote fixture only)
Lumens: 2.5lm
Luminaire efficacy: 6 lm/W

Source: White LED, (LM-80 tested).
3000K: 80 CRI
Lumen maintenance: >70% of initial lumens at 50 000 hours (L70) LM-79 tested.

Optics: Accent light

Mounting: Wall recessed, ground recessed with remote power supply installation.

Material:
Body: Made of highstrength thermoplastic material. Stainless steel screws. Sealed with internal gaskets and a glass lens. Stainless steel trim

Electrical: Supplied with 1'-2" power cable. See remote power supply on page 3.

Dimming: See remote power supply on page 3.


Finish: Stainless Steel

Weight: 0.37lbs (0.17kg).


Warranty: 5 year limited warranty

Certification: cULus

Ratings: IP68, IK09



TOP VIEW




FRONT VIEW


iGuzzini NORTH AMERICA

9320 Boul. St-Laurent, suite 100, Montréal (Québec)
Canada H2N 1N7
P.: 514.523.1339 F.: 514.525.6107
www.iguzzini-na.com

TECHNICAL DATA

Model:	**I.BD72**
Color temp.:	3000K, 80CRI
Optic:	Floor washer
Power input:	0.4W
Lumens:	2.5lm (delivered)
Luminaire efficacy:	6 lm/W





ACCESSORIES (TO BE ORDERED SEPARATELY)

***for installation consult the instruction sheet**

◯ **I.B973** - ALUMINUM CASING FOR INSTALLATION ON CEMENT CONCRETE WALLS + COVER PLATE
☐6-11/16"(169mm) X 3-11/16"(93mm)H



◯ **I.B974** - ALUMINUM CASING FOR STANDARD GROUND INSTALLATION + COVER PLATE
☐5-1/8"(130mm) X 3-9/16"(90mm)H



◯ **I.B975** - PLASTIC CASING FOR INSTALLATION IN GARDENS, ON WALLS, AND IN THE GROUND + COVER PLATE



◯ **I.9579** - ADAPTER FOR OUTER CASING (FOR I.B975)



◯ **I.9580** - ADAPTER FOR OUTER CASING (FOR I.B973 - I.B974)



iGuzzini NORTH AMERICA

9320 Boul. St-Laurent, suite 100, Montréal (Québec)
Canada H2N 1N7
P.: 514.523.1339 F.: 514.525.6107
www.iguzzini-na.com

REMOTE POWER SUPPLY OPTION
(TO BE ORDERED SEPARATELY)

Watts	Min-Max	Voltage	Rated	Dimming protocal	Box dimentions	Max distance	Code
10	25	120V	Indoor	None	6" X 4" X 3" (152 X 102 X 76mm)	20ft (6m)	4444-0024-010-120-ND
10	25	120V	Outdoor	None	7" X 4" X 3" (178 X 102 X 76mm)	20ft (6m)	4548-0024-010-120-ND
25	62	120-277V	Indoor	None	6" X 4" X 3" (152 X 102 X 76mm)	20ft (6m)	4444-0024-025-UNV-ND
25	62	120-277V	Outdoor	None	7" X 4" X 3" (178 X 102 X 76mm)	20ft (6m)	4548-0024-025-UNV-ND
80	11-200 (DIM 73-200)	120V	Outdoor	Leading and trailing edge (ELV and TRIAC)	14" X 5" X 2" (356 X 127 X 51mm)	30ft (9m)	4551-0024-080-120-LTE

* The Total power of all connected luminaires may not be higher than the power of the driver.

ORDERING INFO RESET

____ - 13
MODEL FINISH

MODEL
◯ **I.BD72 -** 3000K, 80CRI

FINISH
● **13 -** Stainless Steel

REMOTE POWER SUPPLY OPTION **(TO BE ORDERED SEPARATELY)**
Requirement for one (1) fixture: 0.4W, 24VDC

◯ **4444-0024-010-120-ND**
◯ **4548-0024-010-120-ND**
◯ **4444-0024-025-UNV-ND**
◯ **4548-0024-025-UNV-ND**
◯ **4551-0024-080-120-LTE**

iGuzzini NORTH AMERICA

9320 Boul. St-Laurent, suite 100, Montréal (Québec)
Canada H2N 1N7
P.: 514.523.1339 F.: 514.525.6107
www.iguzzini-na.com