



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

**CERTIFICATE NO.:** 2021011001430516

**Valid from:** May.25,2023

**Valid until:** Nov.05,2026

**NAME AND REGISTERED ADDRESS OF THE APPLICANT** iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, Italy

**NAME AND REGISTERED ADDRESS OF THE MANUFACTURER** iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, Italy

**NAME AND LOCATION OF THE FACTORY** iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, Italy

**PRODUCT MODEL(S)** Ground Recessed Luminaires For LED Modules (Controlled Port Dimming For Some Type, A.C.  
Supplied Electronic Controlgear For LED Modules, ClassII, IP65/IP67, Suitable For Direct Mounting On  
Normally Flammable Material)  
See Appendix. 220/240V ~ 50/60Hz , Static load 50kN , Rated maximum surface temperature T : 40°C,  
H not exceeding 5mm, Intended usage: In restricted accessible areas (e.g. pedestrians and pedal cycles  
only).

**STANDARDS AND TECHNICAL REQUIREMENTS** GB/T 17743-2021;GB 7000.1-2015;GB 7000.213-2008

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Nov.05,2021

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn)



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2021011001430516

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

不可调光:

EQ69 9W (1×6.6W/LED), EQ70 10W (1×8.3W/LED), EQ71 10W (1×8.3W/LED),  
EQ72 10W (1×8.3W/LED), EQ73 9W (1×6.6W/LED), EQ74 10W (1×8.3W/LED),  
EQ75 10W (1×8.3W/LED), EQ76 10W (1×8.3W/LED), EQ87 9W (1×6.7W/LED),  
EQ88 9W (1×6.7W/LED), EQ89 11.6W (10×0.97W/LED), EQ90 11.6W (10×0.97W/LED),  
EQ91 11.6W (10×0.97W/LED), EQ92 11.6W (10×0.97W/LED),

DALI 调光:

EQ77 9.4W (1×6.1W/LED), EQ78 10.5W (1×8.3W/LED), EQ79 10.5W (1×8.3W/LED),  
EQ80 10.5W (1×8.3W/LED), EQ81 9.4W (1×6.1W/LED), EQ82 10.5W (1×8.3W/LED),  
EQ83 10.5W (1×8.3W/LED), EQ84 10.5W (1×8.3W/LED), EQ85 8.8W (1×6.1W/LED),  
EQ86 8.8W (1×6.1W/LED), EQ93 11.7W (1×7.9W/LED), EQ94 15W (1×12W/LED),  
EQ95 14.5W (1×12W/LED), EQ96 14.5W (1×12W/LED), EQ97 14.5W (1×12W/LED),  
EQ98 11.7W (1×7.9W/LED), EQ99 15W (1×12W/LED), ER00 14.5W (1×12W/LED),  
ER01 14.5W (1×12W/LED), ER02 14.5W (1×12W/LED), ER03 11.9W (1×7.8W/LED),  
ER04 12.1W (1×10W/LED), ER05 12.1W (1×10W/LED), ER06 12.1W (1×10W/LED),  
ER07 11.9W (1×7.8W/LED), ER08 12.1W (1×10W/LED), ER09 12.1W (1×10W/LED),  
ER10 12.1W (1×10W/LED), ER11 15W (1×12W/LED), ER12 15W (1×12W/LED),  
ER13 16.5W (15×1W/LED), ER14 16.5W (15×1W/LED), ER15 16.5W (15×1W/LED),  
ER16 16.5W (15×1W/LED), ER17 14.3W (1×12W/LED), ER18 21.4W (1×18W/LED),  
ER19 21.4W (1×18W/LED), ER20 21.4W (1×18W/LED), ER21 14.3W (1×12W/LED),  
ER22 21.4W (1×18W/LED), ER23 21.4W (1×18W/LED), ER24 21.4W (1×18W/LED),  
ER37 15.8W (1×14W/LED), ER38 15.8W (1×14W/LED), ER39 15.8W (1×14W/LED),  
ER40 15.8W (1×14W/LED), ER41 15.8W (1×14W/LED), ER42 15.8W (1×14W/LED),  
ER43 14.3W (1×12W/LED), ER44 14.3W (1×12W/LED), ER45 23W (20×0.95W/LED),  
ER46 23W (20×0.95W/LED), ER47 23W (20×0.95W/LED), ER48 23W (20×0.95W/LED)。  
220/240V~ 50/60Hz

本灯具额定载荷 50kN, 额定最大表面温度 T: 40℃, 安装后突出地面高度不超过 5mm;

预期的使用区域: 在限制触及的区域, 例如: 仅步行和脚踏车区域。



CHINA QUALITY CERTIFICATION CENTRE



# 中国国家强制性产品认证证书

证书编号: 2021011001430516

发证日期: 2023 年 05 月 25 日

有效期至: 2026 年 11 月 05 日

**认证委托人名称** iGuzzini illuminazione S.p.A.

**及注册地址** Via Mariano Guzzini, 37 62019 Recanati, 意大利

**产品生产者名称** iGuzzini illuminazione S.p.A.

**及注册地址** Via Mariano Guzzini, 37 62019 Recanati, 意大利

**生产企业名称** iGuzzini illuminazione S.p.A.

**及生产地址** Via Mariano Guzzini, 37 62019 Recanati, 意大利

**产品名称和系列、规格、型号** 地面嵌入式 LED 灯具 (部分型号控制端口调光, LED 模块用交流电子控制装置, II 类, IP65/IP67, 适宜直接安装在普通可燃材料表面)

见附件。220/240V~ 50/60Hz, 本灯具额定载荷 50kN, 额定最大表面温度 T: 40°C, 安装后突出地面高度不超过 5mm; 预期的使用区域: 在限制触及的区域, 例如: 仅步行和脚踏车区域。

**产品标准和技术要求** GB/T 17743-2021; GB 7000.1-2015; GB 7000.213-2008

上述产品符合 CNCA-C10-01:2014 认证规则的要求, 特发此证。

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书为变更证书, 证书首次颁发日期: 2021 年 11 月 05 日

经中国合格评定国家认可委员会认可 CNAS C001-P

可通过扫描下方二维码或登录国家认监委网站 (www.cnca.gov.cn) 查验证书信息



签发:

谢肇煦



中国质量认证中心



# 中国国家强制性产品认证证书

证书编号 2021011001430516

第 1 页 共 1 页

本证书及附件应同时使用，信息查验说明见证书页

纸号：

不可调光：

EQ69 9W (1×6.6W/LED), EQ70 10W (1×8.3W/LED), EQ71 10W (1×8.3W/LED),  
EQ72 10W (1×8.3W/LED), EQ73 9W (1×6.6W/LED), EQ74 10W (1×8.3W/LED),  
EQ75 10W (1×8.3W/LED), EQ76 10W (1×8.3W/LED), EQ87 9W (1×6.7W/LED),  
EQ88 9W (1×6.7W/LED), EQ89 11.6W (10×0.97W/LED), EQ90 11.6W (10×0.97W/LED),  
EQ91 11.6W (10×0.97W/LED), EQ92 11.6W (10×0.97W/LED),

DALI 调光：

EQ77 9.4W (1×6.1W/LED), EQ78 10.5W (1×8.3W/LED), EQ79 10.5W (1×8.3W/LED),  
EQ80 10.5W (1×8.3W/LED), EQ81 9.4W (1×6.1W/LED), EQ82 10.5W (1×8.3W/LED),  
EQ83 10.5W (1×8.3W/LED), EQ84 10.5W (1×8.3W/LED), EQ85 8.8W (1×6.1W/LED),  
EQ86 8.8W (1×6.1W/LED), EQ93 11.7W (1×7.9W/LED), EQ94 15W (1×12W/LED),  
EQ95 14.5W (1×12W/LED), EQ96 14.5W (1×12W/LED), EQ97 14.5W (1×12W/LED),  
EQ98 11.7W (1×7.9W/LED), EQ99 15W (1×12W/LED), ER00 14.5W (1×12W/LED),  
ER01 14.5W (1×12W/LED), ER02 14.5W (1×12W/LED), ER03 11.9W (1×7.8W/LED),  
ER04 12.1W (1×10W/LED), ER05 12.1W (1×10W/LED), ER06 12.1W (1×10W/LED),  
ER07 11.9W (1×7.8W/LED), ER08 12.1W (1×10W/LED), ER09 12.1W (1×10W/LED),  
ER10 12.1W (1×10W/LED), ER11 15W (1×12W/LED), ER12 15W (1×12W/LED),  
ER13 16.5W (15×1W/LED), ER14 16.5W (15×1W/LED), ER15 16.5W (15×1W/LED),  
ER16 16.5W (15×1W/LED), ER17 14.3W (1×12W/LED), ER18 21.4W (1×18W/LED),  
ER19 21.4W (1×18W/LED), ER20 21.4W (1×18W/LED), ER21 14.3W (1×12W/LED),  
ER22 21.4W (1×18W/LED), ER23 21.4W (1×18W/LED), ER24 21.4W (1×18W/LED),  
ER37 15.8W (1×14W/LED), ER38 15.8W (1×14W/LED), ER39 15.8W (1×14W/LED),  
ER40 15.8W (1×14W/LED), ER41 15.8W (1×14W/LED), ER42 15.8W (1×14W/LED),  
ER43 14.3W (1×12W/LED), ER44 14.3W (1×12W/LED), ER45 23W (20×0.95W/LED),  
ER46 23W (20×0.95W/LED), ER47 23W (20×0.95W/LED), ER48 23W (20×0.95W/LED)。  
220/240V~ 50/60Hz

本灯具额定载荷 50kN，额定最大表面温度 T：40℃，安装后突出地面高度不超过 5mm；

预期的使用区域：在限制触及的区域，例如：仅步行和脚踏车区域。



中国质量认证中心