



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

**CERTIFICATE NO.:** 2021011001430516

**NAME AND ADDRESS OF THE APPLICANT**

iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, Italy

**NAME AND ADDRESS OF THE MANUFACTURER**

iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, Italy

**NAME AND LOCATION OF THE FACTORY**

iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, Italy

**PRODUCT NAME, MODEL AND SPECIFICATION**

Ground Recessed Luminaires For LED Modules (Controlled Port Dimming For Some Type, A.C.  
Supplied Electronic Controlgear For LED Modules, Class II , IP65/IP67, Suitable For Direct Mounting  
On Normally Flammable Material)

See Appendix. 220/240V ~ 50/60Hz , Static load 50kN , Rated maximum surface temperature T : 40°C, H not exceeding  
5mm, Intended usage: In restricted accessible areas (e.g. pedestrians and pedal cycles only).

**STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS**

GB 17625.1-2022;GB/T 17743-2021;GB 7000.1-2015;GB 7000.213-2008

This is to certify that the above mentioned product(s) complies with the requirements of  
implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014).

**Valid from:** May.12,2025

**Valid until:** Nov.05,2026

Date of original issued: Nov.05,2021

The certificate information and validity could be checked by scanning the QR code below or logging in to  
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).



**SIGNATURE:**

谢肇煦



**中国质量认证中心**  
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，  
不得单独使用  
This translated document  
does not have legal validity and  
cannot be used in isolation

CERTIFICATE NO. : 2021011001430516

Appendix: Page 1 of 1

不可调光:

EQ69 9W(1×6.6W/LED), EQ70 10W(1×8.3W/LED), EQ71 10W(1×8.3W/LED),  
EQ72 10W(1×8.3W/LED), EQ73 9W(1×6.6W/LED), EQ74 10W(1×8.3W/LED),  
EQ75 10W(1×8.3W/LED), EQ76 10W(1×8.3W/LED), EQ87 9W(1×6.7W/LED),  
EQ88 9W(1×6.7W/LED), EQ89 11.6W(10×0.97W/LED), EQ90 11.6W(10×0.97W/LED),  
EQ91 11.6W(10×0.97W/LED), EQ92 11.6W(10×0.97W/LED),

控制端口调光 (DALI 调光):

EQ85 8.8W(1×6.1W/LED), EQ86 8.8W(1×6.1W/LED), EQ93 11.7W(1×7.9W/LED),  
EQ94 15W(1×12W/LED), EQ95 14.5W(1×12W/LED), EQ96 14.5W(1×12W/LED),  
EQ97 14.5W(1×12W/LED), EQ98 11.7W(1×7.9W/LED), EQ99 15W(1×12W/LED),  
ER00 14.5W(1×12W/LED), ER01 14.5W(1×12W/LED), ER02 14.5W(1×12W/LED),  
ER03 11.9W(1×7.8W/LED), ER04 12.1W(1×10W/LED), ER05 12.1W(1×10W/LED),  
ER06 12.1W(1×10W/LED), ER07 11.9W(1×7.8W/LED), ER08 12.1W(1×10W/LED),  
ER09 12.1W(1×10W/LED), ER10 12.1W(1×10W/LED), ER11 15W(1×12W/LED),  
ER12 15W(1×12W/LED), ER13 16.5W(15×1W/LED), ER14 16.5W(15×1W/LED),  
ER15 16.5W(15×1W/LED), ER16 16.5W(15×1W/LED), ER17 14.3W(1×12W/LED),  
ER18 21.4W(1×18W/LED), ER19 21.4W(1×18W/LED), ER20 21.4W(1×18W/LED),  
ER21 14.3W(1×12W/LED), ER22 21.4W(1×18W/LED), ER23 21.4W(1×18W/LED),  
ER24 21.4W(1×18W/LED), ER37 15.8W(1×14W/LED), ER38 15.8W(1×14W/LED),  
ER39 15.8W(1×14W/LED), ER40 15.8W(1×14W/LED), ER41 15.8W(1×14W/LED),  
ER42 15.8W(1×14W/LED), ER43 14.3W(1×12W/LED), ER44 14.3W(1×12W/LED),  
ER45 23W(20×0.95W/LED), ER46 23W(20×0.95W/LED), ER47 23W(20×0.95W/LED),  
ER48 23W(20×0.95W/LED).

220/240V~ 50/60Hz.

本灯具额定载荷 50kN, 额定最大表面温度 T: 40℃, 安装后突出地面高度不超过 5mm;

预期的使用区域: 在限制触及的区域, 例如: 仅步行和脚踏车区域。

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





# 中国国家强制性产品认证证书

证书编号: 2021011001430516

## 认证委托人名称及地址

iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, 意大利

## 生产者名称及地址

iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, 意大利

## 生产企业名称及地址

iGuzzini illuminazione S.p.A.  
Via Mariano Guzzini, 37 62019 Recanati, 意大利

## 产品名称和系列、型号、规格

地面嵌入式 LED 灯具 (部分型号控制端口调光, LED 模块用交流电子控制装置, II 类, IP65/IP67, 适宜直接安装在普通可燃材料表面)  
见附页; 220/240V~ 50/60Hz, 本灯具额定载荷 50kN, 额定最大表面温度 T: 40°C, 安装后突出地面高度不超过 5mm; 预期的使用区域: 在限制触及的区域, 例如: 仅步行和脚踏车区域。

## 产品标准和技术要求

GB 17625.1-2022; GB/T 17743-2021; GB 7000.1-2015; GB 7000.213-2008

上述产品符合《强制性产品认证实施规则 照明电器》(CNCA-C10-01:2014) 的要求, 特发此证。

发证日期: 2025 年 05 月 12 日 有效期至: 2026 年 11 月 05 日

本证书为变更证书, 证书首次颁发日期: 2021 年 11 月 05 日  
证书信息和有效性可扫描下方二维码或登录发证机构网站查验,  
也可在认监委网站 (www.cnca.gov.cn) 查询。



签发:

谢肇煦



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司







# 中国国家强制性产品认证证书

证书编号: 2021011001430516

证书附页: 第 1 页 共 1 页

不可调光:

EQ69 9W(1×6.6W/LED), EQ70 10W(1×8.3W/LED), EQ71 10W(1×8.3W/LED),  
EQ72 10W(1×8.3W/LED), EQ73 9W(1×6.6W/LED), EQ74 10W(1×8.3W/LED),  
EQ75 10W(1×8.3W/LED), EQ76 10W(1×8.3W/LED), EQ87 9W(1×6.7W/LED),  
EQ88 9W(1×6.7W/LED), EQ89 11.6W(10×0.97W/LED), EQ90 11.6W(10×0.97W/LED),  
EQ91 11.6W(10×0.97W/LED), EQ92 11.6W(10×0.97W/LED),

控制端口调光 (DALI 调光):

EQ85 8.8W(1×6.1W/LED), EQ86 8.8W(1×6.1W/LED), EQ93 11.7W(1×7.9W/LED),  
EQ94 15W(1×12W/LED), EQ95 14.5W(1×12W/LED), EQ96 14.5W(1×12W/LED),  
EQ97 14.5W(1×12W/LED), EQ98 11.7W(1×7.9W/LED), EQ99 15W(1×12W/LED),  
ER00 14.5W(1×12W/LED), ER01 14.5W(1×12W/LED), ER02 14.5W(1×12W/LED),  
ER03 11.9W(1×7.8W/LED), ER04 12.1W(1×10W/LED), ER05 12.1W(1×10W/LED),  
ER06 12.1W(1×10W/LED), ER07 11.9W(1×7.8W/LED), ER08 12.1W(1×10W/LED),  
ER09 12.1W(1×10W/LED), ER10 12.1W(1×10W/LED), ER11 15W(1×12W/LED),  
ER12 15W(1×12W/LED), ER13 16.5W(15×1W/LED), ER14 16.5W(15×1W/LED),  
ER15 16.5W(15×1W/LED), ER16 16.5W(15×1W/LED), ER17 14.3W(1×12W/LED),  
ER18 21.4W(1×18W/LED), ER19 21.4W(1×18W/LED), ER20 21.4W(1×18W/LED),  
ER21 14.3W(1×12W/LED), ER22 21.4W(1×18W/LED), ER23 21.4W(1×18W/LED),  
ER24 21.4W(1×18W/LED), ER37 15.8W(1×14W/LED), ER38 15.8W(1×14W/LED),  
ER39 15.8W(1×14W/LED), ER40 15.8W(1×14W/LED), ER41 15.8W(1×14W/LED),  
ER42 15.8W(1×14W/LED), ER43 14.3W(1×12W/LED), ER44 14.3W(1×12W/LED),  
ER45 23W(20×0.95W/LED), ER46 23W(20×0.95W/LED), ER47 23W(20×0.95W/LED),  
ER48 23W(20×0.95W/LED).

220/240V~ 50/60Hz.

本灯具额定载荷 50kN, 额定最大表面温度 T: 40℃, 安装后突出地面高度不超过 5mm;

预期的使用区域: 在限制触及的区域, 例如: 仅步行和脚踏车区域。

本页为证书附页, 应与证书主页同时使用。



中国质量认证中心  
CHINA QUALITY CERTIFICATION CENTRE

中国质量认证中心有限公司