

Product configuration: MQ77.83

Product code

Technical description

Installation

Colour

Black Transparent (83)

Weight (Kg)

0.29

Mounting

meaning
wall recessed|ceiling recessed

Wiring

on control gear box: screw connections with terminal block included


Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	810	CRI (typical):	97
W system:	13	Colour temperature [K]:	4000
lm source:	1000	MacAdam Step:	3
W source:	10	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	62.3	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	81	Number of optical assemblies:	1
Beam angle [°]:	48°	Control:	DALI-2
CRI (minimum):	95		


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	72	68	66	63	68	65	65	62	77
1.0	76	72	69	68	71	69	69	66	81
1.5	80	77	75	73	76	74	73	71	87
2.0	82	80	79	77	79	78	77	74	92
2.5	84	82	81	80	81	80	79	77	95
3.0	85	84	83	82	82	82	81	79	97
4.0	86	85	84	84	84	83	82	80	99
5.0	86	86	85	85	84	84	83	81	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 1000 lm bare lamp luminous flux)											
Reflect.: ceiling walls work pl. Room dim x y		viewed crosswise					viewed endwise				
2H	2H	8.0	9.1	8.9	9.4	9.6	9.2	9.7	9.5	10.0	10.2
	3H	8.8	9.3	9.1	9.5	9.8	9.3	9.7	9.6	10.0	10.3
	4H	8.9	9.3	9.2	9.6	9.9	9.3	9.7	9.6	10.0	10.3
	6H	8.9	9.3	9.3	9.6	9.9	9.2	9.6	9.6	9.9	10.3
	8H	8.9	9.3	9.3	9.6	9.9	9.2	9.6	9.6	9.9	10.2
	12H	8.9	9.3	9.3	9.6	10.0	9.2	9.5	9.5	9.9	10.2
4H	2H	8.7	9.2	9.1	9.4	9.7	9.7	10.1	10.0	10.4	10.7
	3H	9.0	9.4	9.4	9.7	10.1	10.0	10.3	10.3	10.7	11.0
	4H	9.2	9.5	9.6	9.9	10.3	10.1	10.4	10.5	10.8	11.1
	6H	9.3	9.6	9.7	10.0	10.4	10.1	10.4	10.5	10.8	11.2
	8H	9.3	9.6	9.7	10.0	10.4	10.1	10.4	10.5	10.8	11.2
	12H	9.3	9.5	9.8	10.0	10.4	10.1	10.3	10.5	10.7	11.2
8H	4H	9.3	9.5	9.7	10.0	10.4	10.5	10.8	11.0	11.2	11.6
	6H	9.4	9.6	9.9	10.1	10.6	10.7	10.9	11.2	11.4	11.8
	8H	9.4	9.6	9.9	10.1	10.6	10.8	10.9	11.2	11.4	11.9
	12H	9.5	9.7	10.0	10.1	10.7	10.8	10.9	11.3	11.4	11.9
12H	4H	9.3	9.5	9.7	9.9	10.4	10.7	10.9	11.1	11.4	11.8
	6H	9.4	9.6	9.9	10.1	10.6	10.9	11.1	11.4	11.6	12.1
	8H	9.5	9.6	10.0	10.1	10.6	11.0	11.2	11.5	11.7	12.2
Variations with the observer position at spacing:											
S =		1.0H					2.6 / -2.5				
		1.5H					4.5 / -2.8				
		2.0H					6.3 / -3.6				
							1.7 / -1.7				
							3.2 / -2.0				
							4.8 / -2.4				