

Last information update: March 2025

Product configuration: PG53.G1

PG53.G1: Module for Superrail 48V track - DALI - GL - L=916 - - 14.8W 1717lm - 2700K - CRI 90 - Black/Black Transparent

**Product code**

PG53.G1: Module for Superrail 48V track - DALI - GL - L=916 - - 14.8W 1717lm - 2700K - CRI 90 - Black/Black Transparent

Technical description

Linear lighting product with 2700K CRI90 monochrome LED complete with adapter for installation on a Superrail 48V track. General Light (High Output) luminaire with Opti-Diamond Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each light module on the track to be adjusted separately. Frameless version main body made of extruded aluminium. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

Mechanical fastening with adapter on a Superrail 48V track

Colour

Black/Black Transparent (G1)

Weight (Kg)

0.52

Mounting

Low voltage track


Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

lm system:	1555	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	14.8	Voltage [Vin]:	48
lm source:	2020	Lamp code:	LED
W source:	13	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	105.1	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	30	LED current [mA]:	77
Light Output Ratio (L.O.R.) [%]:	77	Power factor:	See installation instructions
CRI (minimum):	90	Minimum dimming %:	5
Colour temperature [K]:	2700	Overvoltage protection:	2kV Common mode & 1kV Differential mode
MacAdam Step:	3	Control:	DALI

Polar

Imax=1639 cd C75-255 Lux					
90°	180°	90°	h	d1	d2 Em Emax
α=60°					
4	4.6	4.6	79	100	
8	9.2	9.2	20	25	
12	13.8	13.9	9	11	
16	18.4	18.5	5	6	

Isolux

