

**Product configuration: Q366+Q405.12**

Q405.12: Plate - General Down Light - Neutral LED - L 896 - 4000K - CRI 80 - Aluminium



Q366: Minimal continuous line module General Down Light L 898

**Technical description**  
Minimal (frameless) version extruded aluminium intermediate profile for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen (diffused general light); screen set up for connecting several lengths by overlapping.

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; mechanical systems for connecting modules included in the package.

Colour	Weight (Kg)
White (01)   Aluminium (12)	2

ceiling recessed|wall surface|ceiling surface|ceiling pendant

**Wiring**  
Set up to house the LED modules required by the system.

Take care with the system configuration. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



Q405.12: Plate - General Down Light - Neutral LED - L 896 - 4000K - CRI 80 - Aluminium **Attention! Code no longer in production**

LED module set up for housing in initial or intermediate system profiles - down emission. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral LED.

Module insertion on profiles facilitated by a quick coupling system.

Colour	Weight (Kg)
Indeterminate (00)   White (01)	1.2

**Quick coupling terminal block connection** to simplify connections between the luminaires. LED module complete with integrated control gear.

Complies with EN60598-1 and pertinent regulations



Im system:	2997	Colour temperature [K]:	4000
W system:	26.3	MacAdam Step:	3
Im source:	4050	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	22	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	114	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	74	Number of optical assemblies:	1
CRI (minimum):	80		

