

Last information update: November 2024

Product configuration: QA92+QB50.01

QA92: Initial moduleMinimal DownGeneral LightL 2397

QB50.01: Down HO plate - ON-OFF - General Light - LED Warm - L 1196 - 24.5W 2845lm - 3000K - White

Product code

QA92: Initial moduleMinimal DownGeneral LightL 2397

Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting and up-down emission; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

Colour

White (01) | Black (04) | Aluminium (12)

Weight (Kg)

4.7

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.
TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



Product code

QB50.01: Down HO plate - ON-OFF - General Light - LED Warm - L 1196 - 24.5W 2845lm - 3000K - White **Attention! Code no longer in production**

Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Indeterminate (00)

Weight (Kg)

1.28

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	5890	CRI (minimum):	80
W system:	49.2	Colour temperature [K]:	3000
lm source:	7750	MacAdam Step:	3
W source:	44	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	119.7	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

