



Product configuration: QA94+QB17.01

QA94: Module for continuous lineMinimal DownGeneral LightL 898

QB17.01: Down LO plate - ON-OFF - General Light - LED Warm - L 896 - 12.5W 1375lm - 3000K - White

**Product code**

QA94: Module for continuous lineMinimal DownGeneral LightL 898

Technical description

Extruded aluminium intermediate profile - Minimal (frameless) version for flush with ceiling mounting; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately; the mechanical systems for connecting the subsequent profiles are included in the package.

Colour	Weight (Kg)
White (01) Black (04) Aluminium (12)	1.66

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request. contact IGuzzini for more info

Complies with EN60598-1 and pertinent regulations



Product code

QB17.01: Down LO plate - ON-OFF - General Light - LED Warm - L 896 - 12.5W 1375lm - 3000K - White **Attention! Code no longer in production**

Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour	Weight (Kg)
Indeterminate (00)	0.99

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1444	CRI (minimum):	80
W system:	13.5	Colour temperature [K]:	3000
Im source:	1900	MacAdam Step:	3
W source:	11	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	107	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	1

Polar

