

Product configuration: QB12+QA90.01

Product code

QB12: Down LO plate - DALI - General Light - LED Neutral - L 598

Technical description

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour
Indeterminate (00)

Weight (Kg)
0.82

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



Product code

QA90.01: Initial module - Minimal Down - General Light - L 612 - White

Technical description

Initial profile in extruded aluminium - Minimal (frameless) version for flush with ceiling mounting and up-down emission; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Installation

Installation can be recessed, surface, ceiling and pendant-mounted using suitable accessories to be ordered separately. The initial modules can be used individually for various applications if completed with accessory caps and the required LED module.

Colour
White (01)

Weight (Kg)	1.21
-------------	------

Mounting

ceiling recessed|ceiling surface|ceiling pendant

Wiring

Setting up the LED modules
Set up to house the LED modules required by the system.

Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iguzzini@iguzzini.com for more info

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1026	Lamp code:	LED
W system:	7.5	Number of lamps for optical assembly:	1
Im source:	1350	ZVEI Code:	LED
W source:	7.5	Number of optical assemblies:	1
Luminous efficiency (Im/W, real value):	136.8	Power factor:	See installation instructions
Im in emergency mode:	-	Inrush current:	18 A / 250 µs
Total light flux at or above an angle of 90° [Lm]:	0	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 21 luminaires B16A: 34 luminaires C10A: 35 luminaires C16A: 57 luminaires
Light Output Ratio (L.O.R.) [%]:	76	Minimum dimming %:	1
CRI (minimum):	80	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	4000	Control:	DALI-2
MacAdam Step:	3		

Polar

