

Last information update: May 2025

#### Product configuration: QB16+QA84.01

QB16: Down LO plate - ON-OFF - General Light - LED Warm - L 598

QA84.01: Initial module - Frame Down - General Light - L 612 - White

#### Product code

QB16: Down LO plate - ON-OFF - General Light - LED Warm - L 598 **Attention! Code no longer in production**

#### Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). Electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

0.82

#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated ON-OFF - non-dimmable control gear.

Complies with EN60598-1 and pertinent regulations



#### Product code

QA84.01: Initial module - Frame Down - General Light - L 612 - White **Attention! Code no longer in production**

#### Technical description

Initial profile in extruded aluminium - Frame version with contact frame; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

#### Installation

Recessed using the brackets on the profile. The initial modules can be used individually (stand-alone), if completed with accessory caps and the required LED module.

#### Colour

White (01)

#### Weight (Kg)

1.41

#### Mounting

ceiling recessed|ceiling pendant

#### Wiring


Set up to house the LED modules required by the system.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



#### Technical data

lm system:	950	CRI (minimum):	80
W system:	7.5	Colour temperature [K]:	3000
lm source:	1250	MacAdam Step:	3
W source:	7.5	Lamp code:	LED
Luminous efficiency (lm/W, real value):	126.7	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	76		

Polar

