

QA84.01: Initial module - Frame Down - General Light - L 612 - White

QB20: Down LO plate - DALI - General Light - LED Warm - L 598


LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

Module insertion on profiles facilitated by a quick coupling system.

Colour	Weight (Kg)
Indeterminate (00)	0.82

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



QA84.01: Initial module - Frame Down - General Light - L 612 - White

Initial profile in extruded aluminium - Frame version with contact frame; methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

Recessed using the brackets on the profile. The initial modules can be used individually (stand-alone), if completed with accessory caps and the required LED module.

Colour	Weight (Kg)
White (01)	1.41

ceiling recessed|ceiling pendant

Set up to house the LED modules required by the system.

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iguzzini@iguzzini.com for more info

Complies with EN60598-1 and pertinent regulations



Im system:	950	Lamp code:	LED
W system:	7.5	Number of lamps for optical assembly:	1
Im source:	1250	ZVEI Code:	LED
W source:	7.5	Number of optical assemblies:	1
Luminous efficiency (Im/W, real value):	126.7	Power factor:	See installation instructions
Im in emergency mode:	-	Inrush current:	18 A / 250 µs
Total light flux at or above an angle of 90° [Lm]:	0	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 21 luminaires B16A: 34 luminaires C10A: 35 luminaires C16A: 57 luminaires
Light Output Ratio (L.O.R.) [%]:	76	Minimum dimming %:	1
CRI (minimum):	80	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2
MacAdam Step:	3		

Polar

