

Last information update: November 2024

#### Product configuration: QB21+QA88.01

QB21: Down LO plate - DALI - General Light - LED Warm - L 896

QA88.01: Module for continuous line - Frame Down - General Light - L 898 - White

#### Product code

QB21: Down LO plate - DALI - General Light - LED Warm - L 896

#### Technical description

LED module set up for housing in initial or intermediate system profiles. Down emission - Low Output version for General Light profiles (with opal diffuser screen). DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

#### Installation

Module insertion on profiles facilitated by a quick coupling system.

#### Colour

Indeterminate (00)

#### Weight (Kg)

0.99

#### Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Complies with EN60598-1 and pertinent regulations



#### Product code

QA88.01: Module for continuous line - Frame Down - General Light - L 898 - White

#### Technical description

Extruded aluminium intermediate profile - Frame version with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

#### Installation

This can be recessed using the brackets on the profile; the mechanical systems for connecting the subsequent profiles are included in the package.

#### Colour

White (01)

#### Weight (Kg)

1.86

#### Mounting

ceiling recessed|ceiling pendant

#### Wiring


Set up to house the LED modules required by the system.

#### Notes

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



#### Technical data

Im system:	1444	CRI (minimum):	80
W system:	11	Colour temperature [K]:	3000
Im source:	1900	MacAdam Step:	3
W source:	11	Lamp code:	LED
Luminous efficiency (Im/W, real value):	131.3	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	76	Control:	DALI-2

Polar

