

Last information update: November 2024

**Product configuration: QB55+QA89.01**

QB55: Down HO plate - DALI - General Light - LED Warm - L 3588

QA89.01: Module for continuous line - Frame Down - General Light - L 3596 - White

**Product code**

QB55: Down HO plate - DALI - General Light - LED Warm - L 3588

**Technical description**

LED module set up for housing in intermediate system profiles, ideal for particularly long light lines. Down emission - High Output version for General Light profiles (with opal diffuser screen). The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

3.8

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations


**Product code**

QA89.01: Module for continuous line - Frame Down - General Light - L 3596 - White

**Technical description**

Extruded aluminium intermediate profile - Frame version with contact frame; this allows continuous lines to be created with other intermediate profiles and an initial profile (required). Methacrylate opal screen for diffused general light; screen set up for connecting several lengths by overlapping.

**Installation**

This can be recessed using the brackets on the profile; the mechanical systems for connecting the subsequent profiles are included in the package.

**Colour**

White (01)

**Weight (Kg)**

7.4

**Mounting**

ceiling recessed/ceiling pendant


**Wiring**

Set up exclusively to house L 3588 triple-length LED modules.

**Notes**

Take care with the system configuration. To make continuous lines of lighting, use the intermediate modules. To complete a continuous line correctly there must always be an initial module at the start or end of the composition. TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations


**Technical data**

lm system:	8854	CRI (minimum):	80
W system:	67	Colour temperature [K]:	3000
lm source:	11650	MacAdam Step:	3
W source:	67	Lamp code:	LED
Luminous efficiency (lm/W, real value):	132.1	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	76	Control:	DALI-2

Polar

