

Last information update: December 2024

**Product configuration: Q423+QH96**

QH96: Plate - Down - Office / Working UGR < 19 - DALI - Warm LED - L 3588

**Product code**

QH96: Plate - Down - Office / Working UGR < 19 - DALI - Warm LED - L 3588

**Technical description**

LED module set up for housing in initial or intermediate system profiles, ideal for particularly long light lines. High efficiency down emission for Working profiles (with a controlled luminance micro-prismatic screen). DALI dimmable electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Warm 3000K LED

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Indeterminate (00)

**Weight (Kg)**

4.1

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	5436.0	Colour temperature [K]:	3000
W system:	45.3	MacAdam Step:	3
lm source:	7550	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W source:	41	Voltage [Vin]:	230
Luminous efficiency (lm/W, real value):	120.0	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	72	Number of optical assemblies:	1
Beam angle [°]:	68° / 78°	Control:	DALI-2
CRI:	80		