


Last information update: April 2025

**Product configuration: R471.83**

R471: Ø 153 - 3000K - CRI80 - UGR&lt;19

**Product code**

R471: Ø 153 - 3000K - CRI80 - UGR&lt;19

**Technical description**

Round fixed luminaire designed to use LED lamps with C.o.B. technology. Version with rim for surface-mounting. Prismatic thermoplastic reflector complete with flux enhancer. Optic available with two finishes, clear white or clear black. Dissipater made of painted grey die-cast aluminium. Product complete with LED lamp in warm white colour tone (3000K) and microfilm that is able to guarantee a light beam of UGR<19 L<3000 cd/m2, which is ideal for environments with video terminals.

**Installation**

Recessed using torsion springs which allow easy installation in false ceilings with thicknesses ranging from 1 mm to 25 mm.

**Colour**

Black Transparent (83)

**Weight (Kg)**

0.68

**Mounting**

ceiling surface

**Wiring**

Product complete with DALI components

**Notes**

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20

IP54

On the visible part of  
the product once installed**Technical data**

Im system:	1402.5	CRI:	80
W system:	11.3	Colour temperature [K]:	3000
Im source:	1650	MacAdam Step:	2
W source:	9.6	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	124.12	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	74°	Control:	DALI-2

