



Last information update: February 2025

Product configuration: RD84.83

RD84.83: 3-cell recessed luminaire - Longitudinal Oval - Transparent/Black

**Product code**

RD84.83: 3-cell recessed luminaire - Longitudinal Oval - Transparent/Black

Installation

recessed with steel wire contrast springs; slot to make in false ceiling: 63 x 183

Colour

Black Transparent (83)

Weight (Kg)

0.4

Mounting

ceiling recessed

Notes

Product for longitudinal, asymmetrical lighting, ideal for environments with a fundamentally linear layout (e.g. corridors, hallways and transit areas)

TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations

IP20

IP43

On the visible part of
the product once installed**Technical data**

lm system: 1179

W system: 8.4

lm source: 1760

W source: 8.4

Luminous efficiency (lm/W,
real value): 140.4

lm in emergency mode: -

Total light flux at or above
an angle of 90° [Lm]: 19Light Output Ratio (L.O.R.) 67
[%]:

CRI (minimum): 80

Colour temperature [K]: 4000

MacAdam Step: 3

Life Time LED 1: > 50,000h - L90 - B10 (Ta 25°C)

Lamp code: LED

Number of lamps for optical
assembly: 1

ZVEI Code: LED

Number of optical
assemblies: 1**Polar**