


Last information update: April 2025

Product configuration: RS78(BR)

RS78: Luminaire L=411,60 - Warm White - CASAMBI - Very Wide Flood (Down) optic - UGR<19

**Product code**

RS78: Luminaire L=411,60 - Warm White - CASAMBI - Very Wide Flood (Down) optic - UGR<19

Technical description

Luminaire made of painted extruded aluminium, frame and caps made of injection-moulded thermoplastic. Very Wide Flood optic (80°) in a Space Opti-Diamond (PMMA) version with a rear cover available in a White (Transparent White) or Black (Transparent Black) version. 3000K CRI80 direct emission monochrome LED lamp (Mid-Power). Version with UGR < 19 controlled luminance - in compliance with the standard for use in environments with video monitors ($L \leq 3000$ cd/m²). Luminaire complete with power supply with CASAMBI Bluetooth technology, frequency 2.4 GHz. The luminaire can be controlled with the Casambi system app and components that enable on-off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's mesh network that allows multiple luminaires to be controlled. Integrated Beacon that can be activated via an app (iBeacon) that enables smart functions for third party applications and the Jiminy Push Notification app. Option of rotation around a vertical axis by 360° with a mechanical rotation lock.

Installation

For an electrified track

Colour

White/White/White Transparent (S1) | Black/White/White
Transparent (S2) | White/Black/Black Transparent (S3) |
Black/Black/Black Transparent (S4)

Weight (Kg)

1.33

Mounting

dali track|three circuit track

Notes

Max Luminaire-Luminaire distance 8 m.

The maximum distance is affected by physical obstacles, like walls, metal panels and the layout of the system.

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

Im system:	2652.0
W system:	18.8
Im source:	3400
W source:	16
Luminous efficiency (Im/W, real value):	141.06
Im in emergency mode:	-
Total light flux at or above an angle of 90° [Lm]:	0.0
Light Output Ratio (L.O.R.) [%]:	78
Beam angle [°]:	72°
CRI:	80
Colour temperature [K]:	3000

MacAdam Step:	3
Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Lamp code:	LED
Number of lamps for optical assembly:	1
ZVEI Code:	LED
Number of optical assemblies:	1
Power factor:	See installation instructions
Inrush current:	5 A / 50 µs
Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
Overvoltage protection:	0kV Common mode & 0kV Differential mode
Control:	Casambi