

Billboard

Design iGuzzini

iGuzzini Bespoke

Last information update: April 2025

Product configuration: SG55

SG55: Pole-mounted system – ASF optic – Neutral White – Midnight – CRI70



Product code

SG55: Pole-mounted system – ASF optic – Neutral White – Midnight – CRI70

Technical description

Outdoor luminaire with direct light street optic. Die-cast aluminium alloy optical assembly with steel spring and 4mm thick tempered glass. Option of $\pm 15^\circ$ tilt adjustment in relation to the road surface. The IP rating is guaranteed by a silicone gasket. The product is supplied with an output cable L=500mm long. The product can be installed with a pole-top or lateral mounting using an attachment (to be purchased separately as an accessory). The component assembly is opened thanks to a hinge, so it is tool-free. The product is equipped with a power supply featuring Midnight protocol. All external screws are made of stainless steel.

Installation

The product can be installed with a pole-top or lateral mounting using an attachment ($\varnothing 60\text{mm}$ o $\varnothing 76\text{mm}$) to be purchased separately as an accessory. Two adapters for $\varnothing 42\text{mm}$ or $\varnothing 46\text{mm}$ poles are also available as accessories.

Colour

Grey (RAL 7010) (U9)


Weight (Kg)

2.74

Mounting

pole-top

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	8590.0	Life Time LED 3:	100,000h - L90 - B10 (Ta 40C)
W system:	52.0	Life Time LED 4:	100,000h - L80 - B10 (Ta 40C)
Im source:	8590	Voltage [Vin]:	230
W source:	48	Lamp code:	LED
Luminous efficiency (Im/W, real value):	165.19	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0.0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	100	Intervallo temperatura ambiente:	from -40°C to 50°C.
Beam angle [°]:	129° / 88°	Power factor:	See installation instructions
CRI:	70	Inrush current:	32 A / 355 µs
Colour temperature [K]:	4000	Minimum dimming %:	5
MacAdam Step:	5	Overvoltage protection:	10kV Common mode & 10kV Differential mode
Life Time LED 1:	100,000h - L90 - B10 (Ta 25C)	Control:	Middle of the night
Life Time LED 2:	100,000h - L80 - B10 (Ta 25C)		