

Last information update: October 2024



Product code

2396: 15 - cell Recessed luminaire - LED - Warm white flood

Technical description

rectangular miniaturised recessed luminaire with 15 optical elements with LED lamps - fixed optics - flood beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare . Supplied with DALI dimmable electronic control gear connected to the luminaire. Warm white LED.

Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 406

Colour

White (01) | Black / Black (43) | Black / White (47)



Mounting

wall recessed|ceiling recessed

Wiring

on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	2663 (*)	CRI:	85
W system:	31 (*)	Colour temperature [K]:	3500
lm source:	3335 (*)	Number of lamps for optical assembly:	1
W source:	31 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	63.84 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2
Beam angle [°]:	34° (*)		