

Constant current power supply unit DALI/Step-Dim/Middle of the night profile IP20 40W - VIN = 120-277VAC 50/60Hz Iout =500mA

Design iGuzzini

iGuzzini

Last information update: October 2023



Accessory code

X214: Constant current power supply unit DALI/Step-Dim/Middle of the night profile IP20 40W - VIN = 120-277VAC 50/60Hz Iout =500mA

Technical description

DALI 40W dimmable electronic ballast, with STEP-DIM, ASTRO-DIM and MIDNIGHT PROFILE functions, Vin=120÷277Vac, 50÷60Hz Vout=18÷56Vdc, Iout=500mA (SELV) IP20 protection rating

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.26	123x79x33

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

Make the connections on the appropriate terminal blocks

Notes

Overvoltage protection: 8KV Common mode, 6KV differenzial mode

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 18 power supply units B16A: 30 power supply units C10A: 31 power supply units C16A: 51 power supply units
Current out [mA]:	500		
Inrush current:	31 A / 186 µs	Minimum dimming %:	10
		Overvoltage protection:	10kV Common mode & 6kV Differential mode