

Project name: \_\_\_\_\_

Type: \_\_\_\_\_



**General information**

**Luminaire characteristics:**

**Power input:** 6.4W

**Lumens:** 191 to 220lm (delivered)

**Luminaire efficacy:** 29 to 39lm/W

**Source:** White LED, 3000K: 80CRI and 4000K: 75CRI.

**Lumen maintenance:** >80% of initial lumens at 50 000 hours (L80) LM-80 (LED) / LM-79 tested.

**Optics:** 360° symmetrical optic with a super-pure aluminum reflector.

**Body:** Die cast aluminum body and stainless steel rods fixed to the base

**Electrical:** High efficiency electronic power supply, rated 50 000 H. 120V or 277V.

**Mounting:** Ground anchored.


**Finish:** Gray (RAL9007)

**Weight:** 8.49lbs (3.85kg.)


**Warranty:** 5 years limited warranty.

**Certification:** cULus listed.

**Ratings:** IP66, IK10.



**TOP VIEW**



**SIDE VIEW**

**ORDERING INFO**

MODEL	VOLTAGE	FINISH	<b>ACCESSORIES (TO BE ORDERED SEPARATELY)</b>	
<input type="radio"/> <b>I.BG21</b> - 4000K <input type="radio"/> <b>I.BG22</b> - 3000K	<input type="radio"/> <b>120</b> - 120V <input type="radio"/> <b>277</b> - 277V	<input type="radio"/> <b>15</b> - Gray	<input type="radio"/> <b>I.B514</b> - Fixing plate with anchor bolts Ø9½" (240mm) x h: 6¾" (163mm)	
			<input type="radio"/> <b>I.B504-02</b> - Black screen for asymmetrical 180° emission	
			<input type="radio"/> <b>I.B506-02</b> - Black screen for 90° + 90° emission	
			<input type="radio"/> <b>I.B508-02</b> - Black screen for 180° emission + light blade	

DUE TO CONTINUOUS IMPROVEMENTS, THE INFORMATION HEREIN MAY BE CHANGED WITHOUT NOTICE.

LAST UPDATE: APRIL 28, 2015

MGD - R2