

## iN60 Evo Stand-alone


Design iGuzzini

iGuzzini

Last information update: July 2025

### Product configuration: RZ44.12

RZ44.12: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - UGR<19 - LO - MMO - L=2400 - 60.3W 7371lm - 3000K - CRI 90 - Aluminium



### Product code

RZ44.12: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - UGR<19 - LO - MMO - L=2400 - 60.3W 7371lm - 3000K - CRI 90 - Aluminium

### Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Warm White LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) version with controlled luminance emission ( $L \leq 3000 \text{ cd/m}^2$ ) ideal for environments with video monitors ( $\text{UGR} < 19$ ). The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Metallised polycarbonate raster. Pendant and power supply cables L=1500

### Installation

Pendant-mounted

### Colour

Aluminium (12)

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	7371	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	60.3	Lamp code:	LED
Im source:	9450	Number of lamps for optical assembly:	1
W source:	54	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	122.2	Number of optical assemblies:	1
Im in emergency mode:	-	Power factor:	See installation instructions
Total light flux at or above an angle of 90° [Lm]:	2612	Inrush current:	24.9 A / 215 $\mu\text{s}$
Light Output Ratio (L.O.R.) [%]:	78	Minimum dimming %:	1
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	3000	Control:	DALI-2
MacAdam Step:	3		

### Polar

