

Palco Recessed / Surface

Last information update: October 2024

Product configuration: QC20
QC20: Palco single recess Ø37 - spot - remote driver



Product code
QC20: Palco single recess Ø37 - spot - remote driver

Technical description
Miniaturised adjustable spotlight for recessed installation. Spotlight body with a die-cast aluminium dissipation system - cast zamak rotation unit - machined aluminium recess base - steel wire fixing springs. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

Installation
Recessed base with surface stop plate - steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole Ø36 mm.


Colour	Weight (Kg)
White (01) Black (04)	0.12

Mounting
wall recessed|ceiling recessed

Wiring
Output cables for connecting to power supply line.

Notes
Technical and anti-glare accessories available.

Complies with EN60598-1 and pertinent regulations



Technical data			
Im system:	450	CRI (minimum):	90
W system:	8.1	Colour temperature [K]:	2700
Im source:	750	MacAdam Step:	2
W source:	8.1	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	55.6	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	60	Number of optical assemblies:	1
Beam angle [°]:	16°	LED current [mA]:	650

