


Last information update: October 2024



**Product code**

2569: Minimal section 3 x 5 LEDs - Wall Washer

**Technical description**

Linear recessed miniaturised luminaire for LED lamps, specialised for vertical wall lighting. The patented optic system guarantees a homogeneous and effective emission on the wall, as well as avoiding shadow zones near the ceiling. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen - black polycarbonate internal perimeter frame. Supplied with a power supply unit connected to the luminaire.

**Installation**

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

**Colour**

Black (04)


**Mounting**

wall recessed|ceiling recessed

**Wiring**

on power supply box: screw connections.

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	1395 (*)	CRI:	90
W system:	31 (*)	Colour temperature [K]:	3500
lm source:	3488 (*)	Number of lamps for optical assembly:	1
W source:	31 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	45.0 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2