


Last information update: October 2023

Product configuration: B751

B751: LED module with Electronic control gear Spot Optic

**Product code**B751: LED module with Electronic control gear Spot Optic **Attention! Code no longer in production****Technical description**

Luminaire designed to produce direct light with LED light sources and spot optic. The body is made of extruded aluminium EN1706AC 46100LF subjected to phosphochromatisation treatment with double primer and passivation at 120°C. The die-cast aluminium end caps are complete with silicone gaskets 50/60 Shore A and are subjected to post-cooling (oven) system 4/6 h at 200°C. The liquid acrylic paint is baked at 150°C and ensures high resistance to the external environment and UV rays. The top of the optical assembly is closed by a hardened transparent colourless soda-lime glass screen (4 mm thick) fixed by silicone and complete with a plate with power LED. Optic with lens in plastic material. The product comes equipped with a plastic-material translucent filter. Nickel-plated brass cable clamp PG11 for single entry of power supply cable. All external screws are made of stainless steel A2. Complete with lamp. Red, green and amber LED available upon request.

Installation

Wall installation by means of brackets and arms that can be extended and adjusted $\pm 90^\circ$. Ceiling installation by means of plate for ceiling or surface application, suspension cables and rigid rods.

Colour

Grey (15)

Mounting

wall surface|ceiling surface|ceiling pendant

Wiring

Electronic control gear inside the fitting 220 ÷ 240V 50 ÷ 60 Hz.

Notes

Accessories available: antiglare screen and installation accessories.

Complies with EN60598-1 and pertinent regulations

**Technical data**

lm system:	1792	Colour temperature [K]:	3200
W system:	37.2	MacAdam Step:	3
lm source:	2163	Life Time LED 1:	50,000h - L70 - B20 (Ta 25°C)
W source:	32	Ballast losses [W]:	5.2
Luminous efficiency (lm/W, real value):	48.2	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	8°	Intervallo temperatura ambiente:	from -20°C to +35°C.
CRI:	80		

Polar

