

Coefficientes de uso

R	77	75	73	71	55	53	33	00	DRR
K0.8	71	68	65	63	67	65	64	62	78
1.0	75	71	69	67	70	68	68	66	83
1.5	78	76	74	72	75	73	72	70	89
2.0	81	79	77	76	78	76	76	73	93
2.5	82	81	80	79	80	79	78	76	96
3.0	83	82	81	81	81	80	79	77	98
4.0	84	83	83	82	82	82	80	79	99
5.0	84	84	84	83	83	82	81	79	100

Curva límite de luminancia




Diagrama UGR

Corrected UGR values (at 1700 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceil/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	2.7	4.8	3.1	5.2	5.5	2.7	4.8	3.1	5.2	5.5
	3H	2.6	4.2	2.9	4.5	4.9	2.6	4.2	2.9	4.5	4.8
	4H	2.5	3.9	2.9	4.2	4.5	2.5	3.8	2.9	4.2	4.5
	6H	2.5	3.5	2.9	3.8	4.2	2.5	3.5	2.9	3.8	4.2
	8H	2.4	3.5	2.8	3.8	4.2	2.4	3.4	2.8	3.8	4.2
	12H	2.4	3.4	2.8	3.8	4.2	2.4	3.4	2.8	3.8	4.1
4H	2H	2.5	3.8	2.9	4.2	4.5	2.5	3.9	2.9	4.2	4.5
	3H	2.4	3.4	2.8	3.8	4.1	2.4	3.4	2.8	3.8	4.1
	4H	2.3	3.3	2.7	3.7	4.1	2.3	3.3	2.7	3.7	4.1
	6H	1.9	3.6	2.4	4.0	4.5	1.9	3.6	2.4	4.0	4.5
	8H	1.8	3.7	2.3	4.1	4.6	1.8	3.7	2.3	4.1	4.6
	12H	1.7	3.7	2.2	4.2	4.7	1.7	3.6	2.2	4.1	4.6
8H	4H	1.8	3.7	2.3	4.1	4.6	1.8	3.7	2.3	4.1	4.6
	6H	1.7	3.5	2.2	4.0	4.5	1.7	3.5	2.2	4.0	4.5
	8H	1.7	3.3	2.2	3.8	4.3	1.7	3.3	2.2	3.8	4.3
	12H	1.9	2.9	2.4	3.4	3.9	1.8	2.9	2.4	3.4	3.9
12H	4H	1.7	3.6	2.2	4.1	4.6	1.7	3.7	2.2	4.2	4.7
	6H	1.7	3.2	2.2	3.7	4.3	1.7	3.3	2.2	3.8	4.3
	8H	1.8	2.9	2.4	3.4	3.9	1.9	2.9	2.4	3.4	3.9
Variations with the observer position at spacing:											
S =	1.0H	6.9 / -11.5					6.9 / -11.5				
	1.5H	9.7 / -11.7					9.7 / -11.7				
	2.0H	11.7 / -11.8					11.7 / -11.8				