

Constant current power supply unit Phase-cut dimm. - IP20 14W - VIN = 220-240VAC 50/60Hz Ø25

Design iGuzzini

iGuzzini

Last information update: July 2024



Accessory code

MY84: Constant current power supply unit Phase-cut dimm. - IP20 14W - VIN = 220-240VAC 50/60Hz Ø25

Technical description

Electronic Power Supply, dimmable TRIAC (Leading Edge) + IGBT (trailing edge) - 700 mA constant current operation. Protection devices: shortcircuits - overloads.

Installation

remote installation.

Colour

Indeterminate (00)

Weight (Kg)

0.16

Dimension (mm) (*)

101.5x49x29

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

700 mA for Ø25 Laser recessed luminaires. Cables secured with push terminals.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60
Current out [mA]:	700
Inrush current:	1.7 A / 40 µs

Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 50 power supply units
	B16A: 80 power supply units
	C10A: 83 power supply units
	C16A: 136 power supply units

Minimum dimming %:	5
--------------------	---

Overvoltage protection:	2kV Common mode & 1kV Differential mode
-------------------------	---