


Last information update: April 2024

Product configuration: QB02

QB02: Angular LED module - Frame Down LO - ON-OFF - General Light - Warm

**Product code**QB02: Angular LED module - Frame Down LO - ON-OFF - General Light - Warm **Attention! Code no longer in production****Technical description**

Angular element for Frame version profiles with contact frame; including a 3000K Warm LED module, Low Output version. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated control gear. Pass-through wiring for continuous lines:

Installation

Recessed using the brackets on the profile.

Colour

White (01)

Weight (Kg)

4.17

Mounting

ceiling recessed

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. Complete with integrated ON-OFF - non-dimmable control gear.

Notes

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	1900	CRI (minimum):	80
W system:	17.1	Colour temperature [K]:	3000
Im source:	1250	MacAdam Step:	3
W source:	7.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	111.1	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	76	Number of optical assemblies:	2

Polar