

LASER BLADE

REMOTE 1, 2 HEAD


**2W (TRIM) - I.MK45-REM / I.MK46-REM / I.MQ75-REM;
2W (TRIMLESS) - I.MT91-REM / I.MT92-REM;
4W (TRIM) - I.MK47-REM / I.MK48-REM / I.MQ76-REM;
4W (TRIMLESS) - I.MT93-REM / I.MT94-REM**

INS-5037

PAGE 1 OF 1
LAST UPDATE: JANUARY 30, 2014

INSTALLATION


ROUGH INSTALLATION



- A - ENGAGE HANGER BARS (4X, **PROVIDED**) IN SLOTS AVAILABLE, CONNECT THEM TOGETHER.
B - FASTEN HANGER BARS TO CEILING INFRASTRUCTURE WITH APPROPRIATE SCREWS (**NOT PROVIDED**).
C - INSTALL CEILING WITH APPROPRIATE CUT-OUT (SEE BELOW).
D - TRIMLESS VERSION ONLY, PLASTER GAPS FOR FINISHING.

FINISH INSTALLATION

- E - FOR OPENING CONNECTION BOX, UNFASTEN THE SCREWS SLIGHTLY AND SLIDE THE CONNECTION BOX COVER OPEN.
F - MAKE ALL CONNECTIONS WITH CONNECTORS INSIDE CONNECTION BOX AND CLAMP CABLES W/ RATCHETING STRAIN RELIEF. CLOSE CONNECTION BOX.
G - PASS CONNECTION BOX IN THE CUT-OUT, LIFT AND HOLD THE CLIPS AND INSTALL THE LUMINAIRE INTO THE CUT-OUT.



*SEE BELOW FOR POWER SUPPLY REQUIREMENTS

MODEL AND CUT-OUT

I.MXXX-REM-XX

MODEL REMOTE TRIM COLOUR

TRIM *POWER SUPPLY REQUIREMENTS


2W	I.MK45 - 2.1W 200 lm, 3V, 700mA, NEUTRAL WHITE LED, MEDIUM OPTIC
	I.MK46 - 2.1W 180 lm, 3V, 700mA, WARM WHITE LED, MEDIUM OPTIC
	I.MQ75 - 2.1W 160 lm, 3V, 700mA, WARM WHITE LED, >CRI 90, MEDIUM OPTIC
4W	I.MK47 - 4.2W 400 lm, 6V, 700mA, NEUTRAL WHITE LED, MEDIUM OPTIC
	I.MK48 - 4.2W 360 lm, 6V, 700mA, WARM WHITE LED, MEDIUM OPTIC
	I.MQ76 - 4.2W 264 lm, 6V, 700mA, WARM WHITE LED, >CRI 90, MEDIUM OPTIC

TRIMLESS *POWER SUPPLY REQUIREMENTS

2W	I.MT91 - 2.1W 200 lm, 3V, 700mA, NEUTRAL WHITE LED, MEDIUM OPTIC
	I.MT92 - 2.1W 155 lm, 3V, 700mA, WARM WHITE LED, >CRI 90, MEDIUM OPTIC
4W	I.MT93 - 4.2W 400 lm, 6V, 700mA, NEUTRAL WHITE LED, MEDIUM OPTIC
	I.MT94 - 4.2W 310 lm, 6V, 700mA, WARM WHITE LED, >CRI 90, MEDIUM OPTIC

TRIM COLOUR

-01	WHITE
-02	BLACK FOR TRIMLESS ONLY
-10	GRAY



	FINISH SECTION	ROUGH SECTION	CUT-OUT (A x B)	ACCESSORY (C x D x E)
TRIM	I.MK45, I.MK46 & I.MQ75	BN5101	1-3/8"x1-3/8" (35mmx35mm)	5"x7"x3" (127mmx178mmx74mm)
	I.MK47, I.MK48 & I.MQ76	BN5102	1-3/8"x2-5/8" (35mmx64mm)	5"x7"x3" (127mmx178mmx74mm)
TRIMLESS	I.MT91, I.MT92	BN5113	1-3/8"x1-3/8" (35mmx35mm)	5"x7"x3" (127mmx178mmx74mm)
	I.MT93, I.MT94	BN5114	1-3/8"x2-5/8" (35mmx64mm)	5"x7"x3" (127mmx178mmx74mm)

CEILING THICKNESS:
5/8" FOR TRIMLESS
MIN: 1/8" TO MAX: 1-1/8" FOR TRIM

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

MR - R1
APP. BY :



9320 Boul. St-Laurent,
suite 100, Montréal (Québec)
Canada H2N 1N7
P.: 514.523.1339 F.: 514.525.6107

LASER BLADE
REMOTE