

Last information update: April 2025

**Product configuration: RU39+RW05**

RW05: Plate with LED - MMO - Up/Down - UGR<19 - LO - DALI - L=1192



**Product code**

RW05: Plate with LED - MMO - Up/Down - UGR<19 - LO - DALI - L=1192

**Technical description**

3500K LED plate with direct (Down) and indirect (Up) light emission in an MMO version. Low Output (LO) version with controlled luminance emission  $L \leq 3000 \text{ cd/m}^2 - \alpha > 65^\circ$ , for use in environments with video monitors (UGR<19) in compliance with EN 12464-1. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. Moulded and metallised polycarbonate raster.

**Installation**

Module insertion on profiles facilitated by a quick coupling system.

**Colour**

Aluminium (12)

**Wiring**

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

**Notes**

Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.  
TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



**Technical data**

Im system:	3806.4	CRI:	90
W system:	30.2	Colour temperature [K]:	3500
Im source:	4880	MacAdam Step:	3
W source:	27	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (Im/W, real value):	126.04	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	1348.99	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	78	Number of optical assemblies:	1
Beam angle [°]:	72° / 71°	Control:	DALI-2