


Last information update: October 2024



**Product code**

R060: Recessed with 5 cells - Flood optic

**Technical description**

Rectangular 5 optic element recessed miniaturised luminaire. LED lamps with different colour temperatures to create a modulated effect. The variation is achieved by mixing an emission of 5 x 2700K LEDs and 5 x 6500K LEDs with a high Colour Rendering Index. Every optic element contains a warm LED and a cool LED, rotated progressively by 72° in order to cover an angle of 360° for 5 LEDs and obtain a perfect mixture on the ground even between products of different sizes. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition - flood beam - optics are integrated in a set-back position in the black anti-glare screen. The structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with an integrated power supply system (DALI DT8) that, without using additional components, allows the colour temperature to be changed by simply pressing a single button. A DALI programmable setup with an intuitive, easy-to-use touch screen can be obtained using the X479 code with the M630 power supply unit. This panel can be controlled in Bluetooth mode using an app that allows system control to be extended to remote devices, like tablets and smartphones.

**Installation**

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141.

**Colour**

White (01) | Black / Black (43) | Black / White (47)

**Weight (Kg)**

0.29


**Mounting**

wall recessed|ceiling recessed

**Wiring**

Control gear units included. Different management systems are available with a separate code. For technical details, properties and connection procedures see the instruction sheet.

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	-	Beam angle [°]:	40 (*)
W system:	-	CRI:	90
lm source:	-	Number of lamps for optical assembly:	1
W source:	-	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1