


Last information update: June 2025

**Product configuration: R354.01**

R354.01: body Ø 117 mm - medium optic - 38.1W 3961lm - 3000K - CRI 90 - White

**Product code**

R354.01: body Ø 117 mm - medium optic - 38.1W 3961lm - 3000K - CRI 90 - White

**Technical description**

Adjustable mediumlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. mediumlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Built-in dimmable DALI ballast. Luminaire complete with C.O.B. technology LED unit in warm white colour 3000K. Anti-scratch reflector made of P.V.D (physical vapour deposition) aluminium that can provide optimum performance in terms of light efficiency. medium optic. Possibility of installing a flat accessory, like a glass cover or an elliptical distribution refractor. Interchangeable reflectors that can be ordered as an accessory.

**Installation**

On an electrified track or special base

**Colour**

White (01)

**Weight (Kg)**

1.1

**Mounting**

three circuit track

**Wiring**

Product complete with DALI components

Complies with EN60598-1 and pertinent regulations



IP20

IP40

With accessory installed

**Technical data**

lm system:	3961	Rf (Colour Fidelity Index):	92
W system:	38.1	Rg (Gamut Index):	99
lm source:	4660	Colour temperature [K]:	3000
W source:	34	MacAdam Step:	2
Luminous efficiency (lm/W, real value):	104	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
lm in emergency mode:	-	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	85	ZVEI Code:	LED
Beam angle [°]:	22°	Number of optical assemblies:	1
CRI (minimum):	90	Control:	DALI-2

**Polar**

Imax=20942 cd		Lux			
h	d	Em	Emax		
2	0.7	4195	5222		
4	1.5	1049	1306		
6	2.2	466	580		
8	3	262	326		

 $\alpha = 21^\circ / 22^\circ$