

Design iGuzzini iGuzzini

Product configuration: MQ46

Product code

Adjustable linear module with LEDs, specifically designed to be housed in the Laser Blade System channel. The steel coupling plate includes the lighting group and the operating components. Module with 10 lighting cells, in die-cast aluminium, adjustable with a practical extraction and rotation system with max inclination +/- 45°. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled luminance (UGR < 19). Supplied with DALI dimmable control gear connected to the luminaire. Warm white high chromatic yield LED: CRI (Ra) > 90 - lifetime with residual lumen at 80% (L80): 50.000 hours - Ta 25°.

Double rotating pin blocking system with return spring to facilitate the insertion in the profile seating. Can be manoeuvred with a screwdriver.

Weight (Kg)
1.3

ceiling recessed

The module is fitted with connectors on both sides for connecting with subsequent modules. For connections at greater distances, there are accessory connectors (code MXN6 - cables not included).

dimming function with pushbutton (TOUCH DIM/PUSH): for this option consult the instructions included in the package

Complies with EN60598-1 and pertinent regulations



Im system:	1478	CRI:	95
W system:	24.5	Colour temperature [K]:	3000
Im source:	1850	MacAdam Step:	3
W source:	21	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	60.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	80	Number of optical assemblies:	1
Beam angle [°]:	32°	Control:	DALI

$I_{\max}=5071 \text{ cd}$	Lux			
	h	d	Em	E _{max}
90°	4	2.3	244	317
180°	8	4.6	61	79
90°	12	6.9	27	35
0°	16	9.2	15	20

Isolux

