

Laser Blade


Design iGuzzini

iGuzzini

Last information update: May 2024

Product configuration: P189

P189: 5 cell Frameless Recessed luminaire - Tunable White - Wide Flood optic



Product code

P189: 5 cell Frameless Recessed luminaire - Tunable White - Wide Flood optic **Attention! Code no longer in production**

Technical description

Minimal rectangular 5 optic element recessed miniaturised luminaire. Using LED lamps at different colour temperatures allows them to be modulated. This variation is achieved by mixing the emission of 3 x 2700K high CRI LEDs and 2 x 5700K high CRI LEDs. Despite the disparity of the lamps when the two end channels are used - 2700K and 5700K - the intensity of the flux emitted is the same. The colour temperature also remains uniform and constant even when different size products are used together. Main body with die-cast aluminium radiant surface; frameless version for mounting flush with the ceiling. Metallised thermoplastic high definition optics - wide flood beam - set back from the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with an integrated (basic) power system that allows the colour temperature to be varied, without using any extra components, but simply by pressing the buttons (max 4 products). Using the 6170 code you can obtain a simple and intuitive DALI / KNX programmable solution with touch-screen. There are also other control systems available with different codes for large systems that require specialised technicians for their programming: the MH97 + MH93 + M102 group can be used for a DALI / KNX programmable solution - the MH97 + MH93 + M618 group can be used to extend the control of the system to remote supports such as tablets and smart phones.

Installation

recessed with steel wire springs on the specific adapter (included) which allows flush-mounting with the ceiling. Adapter for fitting luminaire to false ceilings (12.5 mm thick) with self-tapping screws; subsequent filling and smoothing operations; insertion of luminaire body and stylish finishing. Preparation hole 35 x 139

Colour

White (01) | Black (04) | Burnished chrome (E6)

Weight (Kg)

0.56

Mounting

wall recessed|ceiling recessed

Wiring

Power units included. Various management solutions are available with a separate code. For technical data, properties and connection modes see the instruction sheet.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	704.65	CRI:	0
W system:	16.8	Colour temperature [K]:	Tunable white
lm source:	850	MacAdam Step:	0
W source:	8.9	Life Time LED 1:	50,000h - L90 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	41.94	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	48°	Wavelength [nm]:	0