

Constant current power supply DALI IP20 50W - Vin = 220-240VAC 50/60Hz Iout = 350÷1050 mA

Design iGuzzini

iGuzzini

Last information update: September 2024



Accessory code

BZM4: Constant current power supply DALI IP20 50W - Vin = 220-240VAC 50/60Hz Iout = 350÷1050 mA

Technical description

25/50W multi-current electronic control gear - dimmable DALI - protection devices: thermal, mains overvoltage, overloads. Current set to be created according to the product used - consult the instruction sheet.

Installation

possibility of fixing to surface with screws (not included)

Colour

Indeterminate (00)

Weight (Kg)

0.2

Dimension (mm) (*)

125x80x22

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

for use with Laser Blade range - Laser Blade XS range - Palco Ceiling + Recessed range - to create the correct current set and for the maximum and minimum quantities to be used with this control gear, consult the reference product instruction sheet.

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60	Minimum dimming %:	1
Current out [mA]:	350	Overvoltage protection:	4kV Common mode & 4kV Differential mode
Inrush current:	10 A / 200 µs	Control:	DALI-2
Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 18 power supply units B16A: 30 power supply units C10A: 31 power supply units C16A: 51 power supply units		