

## Constant current power supply DALI IP20 50W - Vin = 220-240VAC 50/60Hz Iout = 350÷1050 mA

Design iGuzzini

iGuzzini

Last information update: December 2023



### Accessory code

BZM4: Constant current power supply DALI IP20 50W - Vin = 220-240VAC 50/60Hz Iout = 350÷1050 mA

### Technical description

25/50W multi-current electronic control gear - dimmable DALI - protection devices: thermal, mains overvoltage, overloads. Current set to be created according to the product used - consult the instruction sheet.

### Installation

possibility of fixing to surface with screws (not included)

### Colour

Indeterminate (00)

### Weight (Kg)

0.2

### Dimension (mm) (\*)

125x80x22

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

### Wiring

for use with Laser Blade range - Laser Blade XS range - Palco Ceiling + Recessed range - to create the correct current set and for the maximum and minimum quantities to be used with this control gear, consult the reference product instruction sheet.

Complies with EN60598-1 and pertinent regulations

IP20

ERC



### Technical data

Frequency [Hz]: 50/60

Current out [mA]: 350

Inrush current: 10 A / 200  $\mu$ s

Maximum number of LED power supply units of this type per miniature circuit breaker:

- B10A: 18 power supply units
- B16A: 30 power supply units
- C10A: 31 power supply units
- C16A: 51 power supply units

Minimum dimming %: 1

Overvoltage protection: 4kV Common mode & 4kV Differential mode

Control: DALI-2