



- Ceiling, wall, or pendant installation.
- Aluminium body turned on a lathe, die-cast aluminium ceiling plate, highly heat-resistant polycarbonate lower frame for ø 240 model, die-cast aluminium frame for ø 140 model.
- Reflectors in super-pure mirror-finish aluminium.
- Professional optics with controlled luminance UGR<19.
- Available electronic multiwatt and DALI control gear, and emergency with inverter.
- High level of light output.
- LED versions with passive dissipation.

Versions



ø 140
H 200



ø 240
H 228




ø 240
H 273




Pendant




Wall-mounted

01
WHITE15
GREY

W	lm	code colour
UGR<19		
LED		
4000K - CRI 80		
9W	1300	MQ06 01-15
3000K - CRI 80		
9W	1300	MQ07 01-15
4000K - CRI 80 - DALI		
9W	1300	MQ08 01-15
3000K - CRI 80 - DALI		
9W	1300	MQ09 01-15




W	lm	code colour
General light		
LED		
4000K - CRI 80		
13W	2000	MQ10 01-15
27W	4000	MQ12 01-15
3000K - CRI 80		
13W	2000	MQ11 01-15
28W	4000	MQ13 01-15
4000K - CRI 80 - DALI		
13W	2000	MQ14 01-15
27W	4000	MQ16 01-15
3000K - CRI 80 - DALI		
13W	2000	MQ15 01-15
28W	4000	MQ17 01-15



W	lm	code colour
UGR<19		
LED		
4000K - CRI 80		
13W	2000	MQ20 01-15
27W	4000	MR73 01-15
27W	4000	MR77 01-15
3000K - CRI 80		
13W	2000	MQ21 01-15
13W	2000	MR76 01-15
28W	4000	MR74 01-15
4000K - CRI 80 - DALI		
13W	2000	MR75 01-15
3000K - CRI 80 - DALI		
28W	4000	MR78 01-15
UGR<19 - with inverter		
LED		
4000K - CRI 80		
13W	2000	MR79 01-15
3000K - CRI 80		
13W	2000	MR80 01-15

accessories

Wall installation mounting
kit

code	colour	code	colour
9439	01-15	9443	01-15

Power supply base with
suspension cables
L=1500

code	colour	code	colour
9438	01-15	9440	01-15
---	---	9441	01-15
---	---	9442	01-15

for DALI versions

for versions with inverter