


Last information update: November 2024

**Accessory code**

PE02: Power supply base with pendant cables - surface-mounted version - for Ø172 body UP-DOWN - UGR < 19 (NOT for PURE versions)

Technical description

Surface-mounted base for BeTwo product pendant mounting/power supply (not to be used for PURE versions). Shaped steel plate for coupling to the ceiling - polycarbonate covering rosette. The pre-arranged wires - L 2,500 mm - simultaneously act as suspension and power supply - the adjustment to the length and the wiring is done in the upper section of the light unit, complete with connection terminal board and safety cable clamps. Sliding devices, to be positioned along the length of the cables, allow the pendant to be aesthetically shaped. Integrated power supply unit consisting of 2 DALI dimmable drivers.

Installation

steel plate for coupling onto the laying surface with screws and anchors (not included)

Colour

White (01) | Black (04)

Weight (Kg)

0.63

Wiring

connection to the network with rapid coupling terminal board positioned on the base unit plate - 2 power supply drivers included with integrated wiring. Adjustment of the power supply/pendant cables and further wiring to be done on the upper section of the light unit, arranged with connecting terminal board and safety cable clamps. Base cannot be used for PURE versions

Complies with EN60598-1 and pertinent regulations



IP40

Technical data

Control: DALI-2