


Last information update: February 2024

Product configuration: 5030

5030: Surface-mounted luminaire - Neutral white - ON-OFF - diffused light



Product code

5030: Surface-mounted luminaire - Neutral white - ON-OFF - diffused light **Attention! Code no longer in production**

Technical description

Diffused light ceiling- / wall-mounted luminaire. LED lamps. Fixing plate made of shaped sheet steel which is painted white. Aluminium LED support acts as a heat sink. Opal PMMA diffuser screen - the shape and finish give uniform, comfortable light emission. Neutral white high efficiency LED

Installation

Ceiling- or wall-mounted. Plate is fixed to surface using screws and screw anchors (not supplied). LED unit removable using easy-lock system. Thermoplastic screen manually fixed on plate with rotation springs.

Colour

White (01)

Weight (Kg)

2.11

Mounting

wall surface|ceiling surface

Wiring

quick-coupling terminal block on fixing plate; set up for pass-through wiring between two or more luminaires; quick-connector links control gear box and removable LED unit.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	2226.0	CRI:	80
W system:	17.0	Colour temperature [K]:	4000
lm source:	2650	MacAdam Step:	3
W source:	15	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25C)
Luminous efficiency (lm/W, real value):	130.94	Ballast losses [W]:	2.0
lm in emergency mode:	-	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	137.34	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	84	ZVEI Code:	LED
Beam angle [°]:	118°	Number of optical assemblies:	1