

# Platea Pro

Design Jean-Michel Wilmotte

iGuzzini

Last information update: November 2024

**Product configuration: P815**  
P815: Platea Pro



**Product code**  
P815: Platea Pro

### Technical description

Outdoor luminaire with an Elliptical optic, designed to use LED lamps. Made up of an optical assembly with a base and an aluminium alloy frame. The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. With a 5 mm thick colourless transparent tempered sodium-calcium glass cover. The product can be tilted by +5°/-90° around the vertical plane with a 10° step graduated gauge and fitted with mechanical blocks that guarantee stable aiming of the beam of light. Horizontal aiming is performed using the slots in the base, which allow an ±30° adjustment. High visual comfort. Polymer optic lenses offering high yield and even light distribution. Complete with circuit fitted with Warm White monochrome power LEDs. Extractable control gear connected with quick-coupling connectors. 220-240V ac 50/60Hz DALI electronic ballast. Replaceable control gear. All the screws used are made of A2 stainless steel.

### Installation

The luminaire can be installed at ground level or on walls using the standard base.

### Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

### Weight (Kg)

8.55

### Mounting

wall arm|wall surface|ground anchored


### Wiring

Luminaire ready for pass-through wiring. Product perfect watertightness at the power cable entry point is guaranteed by 2 nickel-plated brass M24x1.5 cable clamps, suitable for cables with a max external 16mm ø (1.5mm² cross section). Push in terminal board.

### Notes

Available accessories include: a refractor for elliptical light flow distribution, diffusing glass, visor, directional flaps, protective grille .

Complies with EN60598-1 and pertinent regulations



### Technical data

|  |                                |  |   |
|--|--------------------------------|--|---|
| lm system:   | 4449                           | Life Time LED 2:   | 87,000h - L80 - B10 (Ta 40°C)   |
| W system:  | 55.4                           | Lamp code:   | LED   |
| lm source:   | 6450                           | Number of lamps for optical assembly:                                    | 1   |
| W source:  | 51                             | ZVEI Code:   | LED   |
| Luminous efficiency (lm/W, real value):            | 80.3                           | Number of optical assemblies:  | 1   |
| lm in emergency mode:                              | -                              | Intervallo temperatura ambiente:   | from -30°C to 50°C.   |
| Total light flux at or above an angle of 90° [Lm]: | 0                              | Power factor:  | See installation instructions   |
| Light Output Ratio (L.O.R.) [%]:                   | 69                             | Inrush current:  | 62 A / 202 µs   |
| Beam angle [°]:                                    | 58° / 12°                      | Maximum number of luminaires of this type per miniature circuit breaker: | B10A: 6 luminaires<br>B16A: 10 luminaires<br>C10A: 10 luminaires<br>C16A: 17 luminaires |
| CRI (minimum):                                     | 80                             | Minimum dimming %:   | 10  |
| Colour temperature [K]:                            | 3000                           | Overvoltage protection:  | 10kV Common mode & 6kV Differential mode  |
| MacAdam Step:                                      | 3                              | Control:   | DALI-2  |
| Life Time LED 1:                                   | 100,000h - L80 - B10 (Ta 25°C) |  |   |

### Polar

| Imax=16351 cd<br>C0-180 | Lux |      |     |     |      |
|-------------------------|-----|------|-----|-----|------|
|                         | h   | d1   | d2  | Em  | Emax |
| 90°                     | 8   | 8.9  | 1.7 | 179 | 255  |
| 17500                   | 16  | 17.7 | 3.4 | 45  | 64   |
|                         | 24  | 26.6 | 5   | 20  | 28   |
| 0°                      | 32  | 35.5 | 6.7 | 11  | 16   |

$\alpha = 58^\circ / 12^\circ$

Isolux

