

Twilight


Design iGuzzini

iGuzzini

Last information update: May 2024

Product configuration: E216

E216: Pole-mounted system for urban and residential parks and gardens.



Product code

E216: Pole-mounted system for urban and residential parks and gardens. **Attention! Code no longer in production**

Technical description

Outdoor luminaire with a symmetrical optic, designed to use LED lamps. Version with cut-off that eliminates skyward flux dispersion. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Diffuser made of shockproof, UV-stabilised injection moulded polycarbonate. Complete with circuit fitted with monochrome LEDs. Optical assembly consisting of an anodized super-pure aluminium upper reflector, a methacrylate lens and a lower reflector made of metallised PC. Replaceable LEDs and driver. Electronic DALI driver with automatic internal temperature control system. All external screws are made of stainless steel.

Installation

The luminaire can be installed with a pole-top mounting on poles with \varnothing 60mm and 76mm end part using X102 and X126 accessories. Secured to the pole by two bolts.

Colour

Grey (15)

Weight (Kg)

4.89

Mounting

pole-top

Wiring

The product is supplied wired and with an outlet cable 1500mm long.

Notes

Overvoltage protection: 5KV Common Mode, 4KV Differential Mode

Complies with EN60598-1 and pertinent regulations



IK10

IP66



Technical data

Im system:	3030.0	MacAdam Step:	2
W system:	30.7	Life Time LED 1:	52,000h - L90 - B10 (Ta 25C)
Im source:	3030	Life Time LED 2:	100,000h - L80 - B10 (Ta 25C)
W source:	27	Life Time LED 3:	41,000h - L90 - B10 (Ta 40C)
Luminous efficiency (Im/W, real value):	98.7	Life Time LED 4:	100,000h - L80 - B10 (Ta 40C)
Im in emergency mode:	-	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	0.0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	100	ZVEI Code:	LED
Beam angle [°]:	150° / 148°	Number of optical assemblies:	1
CRI:	80	Intervallo temperatura ambiente:	from -40°C to 40°C.
Colour temperature [K]:	3000	Control:	DALI