

## View Opti Beam Lens square

Design iGuzzini /  
Arup

iGuzzini

Last information update: May 2024

### Product configuration: Q326

Q326: square small body spotlight - super spot



### Product code

Q326: square small body spotlight - super spot **Attention! Code no longer in production**

### Technical description

Indoor adjustable spotlight with adapter for installation on a three-phase/DALI track. Device made of die-cast aluminium and a front part made of a thermoplastic material. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Optical assembly consisting of Neutral White tone 4000K LEDs with OPTIBEAM LENS technology and a well-defined super spot light beam. Dimmable DALI driver built-in to box with a semi-hidden system on track. Option of installing a range of flat accessories including an OPTIBEAM REFRACTOR for varying light distribution, an elliptical distribution refractor, a louver, a soft lens and an outdoor accessory like an asymmetric visor for eliminating stray light dispersion on the ceiling.

### Installation

On a three-phase/DALI electrified track

### Colour

Black (04) | Black / White (47)

### Weight (Kg)

1.13


### Mounting

dali track|three circuit track

### Wiring

Product complete with DALI dimmable components, housed in a semi-hidden box on the track.

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	550	CRI:	80
W system:	14.8	Colour temperature [K]:	4000
Im source:	1100	MacAdam Step:	2
W source:	10	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	37.2	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	50	Number of optical assemblies:	1
Beam angle [°]:	8°	Control:	DALI

### Polar

Imax=20161 cd		Lux			
90°	180°	h	d	Em	Emax

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	44	42	40	39	42	40	40	38	76
1.0	46	44	43	41	44	42	42	40	81
1.5	49	47	46	45	47	46	45	43	87
2.0	51	49	48	47	49	48	47	46	92
2.5	52	51	50	49	50	49	49	47	95
3.0	52	52	51	50	51	50	50	48	97
4.0	53	52	52	52	52	51	51	49	98
5.0	53	53	53	52	52	52	51	50	100

Luminance curve limit

