


Ultimo aggiornamento delle informazioni: Dicembre 2024

Configurazione di prodotto: BQ50

BQ50: Linealuce Mini - Wall-/Ceiling-mounted - LED - 48V dc with DMX512-RDM control - L=1511mm - Wall Grazing Optic

**Codice prodotto**

BQ50: Linealuce Mini - Wall-/Ceiling-mounted - LED - 48V dc with DMX512-RDM control - L=1511mm - Wall Grazing Optic

Descrizione tecnica

Direct light luminaire, designed to use WRGBW LED lamps (White, Red, Green, Blue, White), 48V dc with DMX512-RDM control. Ceiling- and wall-mounted. Consists of a body, a box for DMX driver and supports for installation (to be ordered separately). Extruded aluminium body and side box, with zamak die-cast end caps complete with silicone seals. Coated with liquid acrylic paint with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED plate in WRGBW (White, Red, Green, Blue, White), side box with 48V dc DMX512-RDM electronic driver (ballast to be ordered separately). Side box with double PG13.5 cable gland and outlet cables for pass-through wiring. Fitted with a PMMA diffusing filter and optics with plastic (methacrylate) lens for Wall Grazing lighting. All external screws used are made of A2 stainless steel. The luminaire technical characteristics conform to EN 60598-1 standards and particular requirements.

Installazione

The following accessories are available for installation: adjustable wall-mounted arms in AISI304 stainless steel (200mm code BZJ8) and a plate for surface- or ceiling-mounting made of anodised aluminium (BZJ7).

Colore

Grigio (15)

Peso (Kg)

2.87

Montaggio

ad applique|a parete|a soffitto

Cablaggio

The product is equipped with a nickel-plated brass PG13.5 double cable gland with H07RN-F rubber outlet cables 5x1.5mm² for pass-through wiring: each cable is set up both for the DMX-RDM signal and for 48V dc power supply. Available for electrical connection: IP68 5-pin linear connector (BZS6), cap for IP68 connectors + 120 Ohm terminating resistor (BZQ7), 48V dc DIN bar electronic ballasts to be ordered separately: 120W (BZ14), 240W (BZ15) and 480W (BZ16). DMX specifications require the insertion of a 120 Ohm terminating resistor to be placed between the DATA+ and DATA- cables of the last product in the line (code BZQ7)

Note

Product complete with LED lamp. DMX specifications require the insertion of a 120 Ohm terminating resistor to be placed between the DATA+ and DATA- cables of the last product in the line (code BZQ7)

Soddisfa EN60598-1 e relative note



IK05

IP66



ERC




pending

Dati tecnici

Im di sistema:	1548	Life Time LED 2:	50,000h - L80 - B20 (Ta 40°C)
W di sistema:	38.9	Voltaggio [Vin]:	48
Im di sorgente:	2820	Codice lampada:	LED
W di sorgente:	37	Numero di lampade per vano ottico:	1
Efficienza luminosa (lm/W, dati di sistema):	39.8	Codice ZVEI:	LED
Im in modalità emergenza:	-	Numero di vani ottici:	1
Flusso totale emesso a 90° o superiore [Lm]:	0	Intervallo temperatura ambiente operativa:	da -30°C a 50°C.
Light Output Ratio (L.O.R.) [%]:	55	Corrente LED [mA]:	235
Temperatura colore [K]:	WRGBW	Power factor:	Vedi istruzioni di installazione
Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)	Control:	DMX-RDM

Polare



Illuminamenti

Lux		Wall distance = 1m																			
3																					
		0.3	0.6	1	3	7	10	8	4	2	0.7	0.4									
2		1	3	6	10	17	22	19	12	6	3	2									
		2	4	8	14	24	30	25	16	9	5	3									
1		3	5	8	15	24	30	25	16	9	6	3									
		3	5	9	14	21	26	21	15	10	6	4									
0																					
	m	-2	-1	0	1	2	3														