


Last information update: August 2025

Product configuration: RQ68

RQ68: Ø86mm body - BLE Casambi - SuperSpot optic

**Product code**

RQ68: Ø86mm body - BLE Casambi - SuperSpot optic

Technical description

Adjustable spotlight with adapter for installation on an electrified track. High chromatic yield LED lamp (CRI97) with 3000K tone and OptiBeam Lens optic system and SuperSpot optic. Luminaire made of die-cast aluminium and thermoplastic material that allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane with mechanical aiming locks. Passive heat dissipation. Spotlight with "Push&Go" system designed to hold up to three flat accessories at the same time. The same system can also be used to apply another external component selected from the directional flaps and anti-glare screen. All internal accessories rotate 360° about the spotlight longitudinal axis. Body complete with dimmable power supply unit and Casambi protocol positioned inside the product track adapter. The components used allow the products to be controlled with the Casambi system app and components, enabling on-off, dimming and scene recall functions and allowing multiple luminaires to operate in a Casambi mesh network. 2.4 GHz bluetooth frequency. The app is available on the Apple Store and Google Play Store. Integrated Beacon that can be activated via an app (iBeacon) that enables smart functions for third party applications and the Jiminy Push Notification app.

Installation

Installation on an electrified track.

Colour

White (01) | Black (04)

Weight (Kg)

0.92

Mounting

wall surface|ceiling surface

Notes

Max distance between product and product 8 m.

The maximum distance is affected by physical obstacles, like walls, metal panels and the layout of the system.

Complies with EN60598-1 and pertinent regulations



IP20

IP40

for optical
assembly**Technical data**

Im system:	437	MacAdam Step:	2
W system:	14	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	910	Lamp code:	LED
W source:	11	Number of lamps for optical assembly:	1
Luminous efficiency (Im/W, real value):	31.2	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	48	Inrush current:	5 A / 50 µs
Beam angle [°]:	7.2°	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 31 luminaires B16A: 50 luminaires C10A: 52 luminaires C16A: 85 luminaires
CRI (minimum):	97	Overvoltage protection:	4kV Common mode & 2kV Differential mode
Colour temperature [K]:	3000	Control:	Casambi

Polar

Imax=18243 cd		Lux			
90°	180°	h	d	Em	E _{max}
		2	0.3	3357	4561
		4	0.5	839	1140
		6	0.8	373	507
		8	1	210	285