Design iGuzzini

iGuzzini

Last information update: September 2020

Product configuration: 5207+L038 5207: Mini Reglette T16



30

43

## Product code 5207: Mini Reglette T16 Attention! Code no longer in production

## Technical description

High output luminaire for general lighting designed to use T16 fluorescent lamps. Extruded aluminium component-holding box. Polycarbonate standard protective screen. Joints for direct electric and mechanical connection included with the product. Simplified installation and maintenance. Ceiling/wall mounting kit included with the product. T16 fluorescent lamp included with colour temperature 4000°K.

Installation Ceiling- and		ounted.			
Colour White (01	)				
Mounting wall surfa		surface			
Wiring The lumin	aire has a	n electronic t	pallast		
					 Complies with EN60598-1 and pertinent regulations
	960°C	IP20	CE	EAC	

Technical data					
Im system:	1102,2	Colour temperature [K]:	4000		
W system:	16	Ballast losses [W]:	2		
Im source:	1200	Voltage [Vin]:	230		
W source:	14	Lamp code:	L038		
Luminous efficiency (Im/W,	68,9	Socket:	G5		
real value):		Number of lamps for optical	1		
Im in emergency mode:	-	assembly:			
Total light flux at or above	239,3	ZVEI Code:	T 16		
an angle of 90° [Lm]:		Number of optical	1		
Light Output Ratio (L.O.R.) [%]:	92	assemblies:			
CRI:	86				

## Polar

	lmax=191 cd/Klm	C0-180 γ=29°	Lux/K	lm			
		80°	h	d1	d2	Em	Emax
	90°		1	-	2.3	91	185
	225		2	-	4.6	23	46
14 W			3	-	6.9	10	21
≠= T 16 - G5	$\alpha = 180^{\circ} / 98^{\circ}$	•	4	-	9.2	6	12

