Design iGuzzini

iGuzzini

Last information update: August 2025

Product configuration: QJ34

QJ34: Minimal 10 cells - Flood beam - LED



Product code


QJ34: Minimal 10 cells - Flood beam - LED

Technical description

Linear miniaturised recessed luminaire with 10 optical elements for LED lamps - fixed optic. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient luminous flux and a high level of controlled glare visual comfort. Main body with die-cast aluminium radiant surface, minimal (frameless) version for mounting flush with the ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Metallised, thermoplastic, high definition Opti Beam reflector, integrated in a set-back position in the anti-glare screen. Supplied with a dimmable DALI power supply unit connected to the luminaire.

Installation

The luminaire is recessed in the specific adapter (QJ92) by means of a steel wire spring, previously installed on the ceiling that can be 12.5 / 15 / 20 mm thick. A special protective sheath allows finishing operations on the plasterboard to be simplified and speeded up







Colour

White (01) | Black (04) | Gold (14)* | Burnished chrome (E6)*

Weight (Kg)

0.46

* Colours on request

Mounting

wall recessed|ceiling recessed

Wiring

On the power supply unit with terminal board included.

Notes

The special steel wire spring provided is required to facilitate the eventual extraction of the recessed body once it has been inserted.

Complies with EN60598-1 and pertinent regulations





















_		data

Im system:	1411	Colour temperature [K]:	2700		
W system:	23.1	MacAdam Step:	2		
Im source:	1700	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)		
W source:	20	Voltage [Vin]:	230		
Luminous efficiency (lm/W,	61.1	Lamp code:	LED		
real value):		Number of lamps for optical	1		
Im in emergency mode:	-	assembly:			
Total light flux at or above	0	ZVEI Code:	LED		
an angle of 90° [Lm]:		Number of optical	1		
Light Output Ratio (L.O.R.)	83	assemblies:			
[%]:		Control:	DALI-2		
Beam angle [°]:	43°				
CRI (minimum):	90				


Polar

Imax=2898 cd		Lux			
	nL 0.83 100-100-100-100-83	h	d	Em	Emax
	UGR <10-<10 DIN A.61 UTE	2	1.5	590	719
	0.83A+0.00T F"1=999	4	3.1	147	180
3000	F"1+F"2=1000 F"1+F"2+F"3=1000 CIBSE	6	4.6	66	80
α=42°	LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @	_{65°} 8	6.1	37	45

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	80	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	87	85	83	100

Luminance curve limit



Corre	ected UC	R value:	s (at 170	0 Im bar	e lamp li	ım ino us	flux)				
Rifled	ct.:										
ce il/c	av	0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.3
work	pl.	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.2
Roon	n dim	5000000		viewed			67.50/60/7		viewed		
X	У		(crosswis	e	endwise					
2H	2H	6.9	7.4	7.2	7.6	7.8	6.9	7.4	7.2	7.6	73
	ЗН	6.8	7.2	7.1	7.5	7.7	6.8	7.2	7.1	7.5	7.
	4H	6.7	7.1	7.0	7.4	7.7	6.7	7.1	7.0	7.4	7.
	бН	6.6	7.0	7.0	7.3	7.6	6.6	7.0	7.0	7.3	7.
	нв	6.6	7.0	7.0	7.3	7.6	6.6	7.0	7.0	7.3	7.
	12H	6.6	6.9	6.9	7.3	7.6	6.6	6.9	6.9	7.2	7.
4H	2H	6.7	7.1	7.0	7.4	7.7	6.7	7.1	7.0	7.4	7.
	ЗН	6.6	6.9	6.9	7.2	7.6	6.6	6.9	6.9	7.2	7.
	4H	6.5	6.8	6.9	7.1	7.5	6.5	6.8	6.9	7.1	7.5
	бН	6.4	6.7	6.8	7.0	7.5	6.4	6.7	6.8	7.0	7.
	HS	6.3	6.6	6.8	7.0	7.4	6.3	6.6	6.8	7.0	7.
	12H	6.3	6.5	8.8	7.0	7.4	6.3	6.5	6.7	6.9	7.
вн	4H	6.3	6.6	6.8	7.0	7.4	6.3	6.6	6.8	7.0	7.
	6H	6.2	6.5	6.7	6.9	7.4	6.3	6.5	6.7	6.9	7.
	нв	6.2	6.4	6.7	6.8	7.3	6.2	6.4	6.7	6.8	7.
	12H	6.2	6.3	6.7	8.6	7.3	6.2	6.3	6.7	8.6	7.
12H	4H	6.3	6.5	6.7	6.9	7.4	6.3	6.5	8.6	7.0	7.
	6H	6.2	6.4	6.7	6.8	7.3	6.2	6.4	6.7	6.9	7.
	HS	6.2	6.3	6.7	6.8	7.3	6.2	6.3	6.7	6.8	7.
Varia	tions wi	th the ol	bserver	osition a	at spacir	ıg:					
S =	1.0H	7.0 / -14.5					7.0 / -14.5				
	1.5H	9.8 / -14.7					9.8 / -14.7				