



Last information update: May 2024

**Product configuration: MR25**

MR25: Medium body spotlight - warm white - electronic ballast and dimmer - medium optic

**Product code**MR25: Medium body spotlight - warm white - electronic ballast and dimmer - medium optic **Attention! Code no longer in production****Technical description**

Adjustable spotlight with adapter for installation on mains electrified track for high output LED lamp with monochrome emission in a warm white (3000K) colour. Dimmable electronic ballast. The luminaire is made of die-cast aluminium and thermoplastic material, and allows 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. The luminaire has mechanical aiming locks and graduated scales for both movements, operated using the same tool on two screws, one on the optic compartment and one on the adapter for the track. Spotlight equipped with accessory holding ring designed to contain a flat accessory. Another external component can also be applied, selected from directional flaps and an asymmetric screen. All external accessories rotate 360° about the spotlight longitudinal axis.

**Installation**

On an electrified track

**Colour**

White (01) | Grey / Black (74)

**Mounting**

three circuit track

**Wiring**

The dimmable electronic components are housed in the luminaire.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	2565	CRI (minimum):	90
W system:	31	Colour temperature [K]:	3000
Im source:	3300	MacAdam Step:	2
W source:	29	Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	82.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	78	Number of optical assemblies:	1
Beam angle [°]:	14°	Control:	Completo di dimmer

**Polar**

Imax=18967 cd		Lux			
90°	180°	90°	h	d	Em Emax
		20000	2	0.5	3669 4742
			4	1	917 1185
			6	1.5	408 527
			8	2	229 296