


Last information update: October 2024



Product code

2492: Recessed Frame section 5 LEDs - integrated ON-OFF - Wall Washer Longitudinal Glare Control

Technical description

Miniaturized recessed linear luminaire for LED lamps. Asymmetrical optic system designed to achieve effective light distribution on walls and avoid any shadow zones near the ceiling. The black polycarbonate perimeter frame is designed to significantly reduce the effect of longitudinal glare. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Flux enhancer - superpure aluminium reflector - textured PMMA screen. Supplied with a power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141. To light walls correctly check the installation distances and centre-to-centre distances indicated on the instructions sheet.

Colour

Black / Black (43) | Black / White (47)



Mounting

wall recessed|ceiling recessed

Wiring

ON-OFF integrated ballast. Connection to mains network on power supply box; screw connections.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	356 (*)	CRI:	90
W system:	10 (*)	Colour temperature [K]:	3500
lm source:	1112 (*)	Number of lamps for optical assembly:	0
W source:	10 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	35.0 (*)	Number of optical assemblies:	1
lm in emergency mode:	-		