

iN60 Evo Stand-alone

Design iGuzzini

iGuzzini

Last information update: July 2025

Product configuration: RZ14.L2

RZ14.L2: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - UGR<19 - LO - MPO - L=1200 - 13.6W 1519.2lm - 3000K - CRI 90 - White / Opal White

Product code

RZ14.L2: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - UGR<19 - LO - MPO - L=1200 - 13.6W 1519.2lm - 3000K - CRI 90 - White / Opal White

Technical description

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Warm White LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) controlled luminance version ($L \leq 3000 \text{ cd/m}^2$) ideal for environments with video monitors. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Microprismatic PMMA diffuser screen. Pendant and power supply cables L=1500

Installation

Pendant-mounted

Colour

White / Opal White (L2)


Complies with EN60598-1 and pertinent regulations



IP20

CE

UK
CA



Technical data

lm system:	1519	Colour temperature [K]:	3000
W system:	13.6	MacAdam Step:	3
lm source:	2110	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	12	Lamp code:	LED
Luminous efficiency (lm/W, real value):	111.7	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	748	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	72	Control:	DALI-2
CRI (minimum):	90		

Polar

