


Product configuration: MQ42

MQ42: adjustable 5-cell module - LED - integrated DALI dimmable control gear - neutral white - beam 48° **Attention! Code no longer in production**

Adjustable linear module with LEDs, specifically designed to be housed in the Laser Blade System channel. The steel coupling plate includes the lighting group and the operating components. Module with 5 lighting cells, in die-cast aluminium, adjustable with a practical extraction and rotation system with max inclination $\pm 45^\circ$. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled luminance ($UGR < 19$). Supplied with DALI dimmable control gear connected to the luminaire. Neutral white LED - lifetime with residual flow at 80% (L80): 50.000 hours - Ta 25°.

Double rotating pin blocking system with return spring to facilitate the insertion in the profile seating. Can be manoeuvred with a screwdriver.



Weight (Kg)
0.9

ceiling recessed

The module is fitted with connectors on both sides for connecting with subsequent modules. For connections at greater distances, there are accessory connectors (code MXN6 - cables not included).

Complies with EN60598-1 and pertinent regulations



Im system:	829	CRI:	95
W system:	13	Colour temperature [K]:	4000
Im source:	1000	MacAdam Step:	3
W source:	10	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	63.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	83	Number of optical assemblies:	1
Beam angle [°]:	48°	Control:	DALI

<p>$I_{\max}=1469 \text{ cd}$</p> <p>90° 180° 90°</p> <p>1500</p> <p>0°</p> <p>$\alpha=48^\circ$</p>	CIE nL 0.83 100-100-100-100-83 UGR <10-<10 DIN A.61 UTE 0.83A+0.00T F*1=999 F*1+F*2=1000 F*1+F*2+F*3=1000	Lux				
			h	d	Em	E _{max}
		1	0.9	1230	1465	
		2	1.8	307	366	
		3	2.7	137	163	
	4	3.6	77	92		

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	75	71	68	66	70	68	68	65	78
1.0	78	75	72	70	74	72	71	69	83
1.5	82	79	77	76	79	77	76	74	89
2.0	85	83	81	80	82	80	79	77	93
2.5	86	85	84	83	84	83	82	79	96
3.0	87	86	85	85	85	84	83	81	98
4.0	88	87	87	86	86	86	84	82	99
5.0	89	88	88	88	87	86	85	83	100

UGR diagram

Corrected UGR values (at 1000 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	1.8	2.3	2.1	2.5	2.8	1.8	2.3	2.1	2.5	2.8
	3H	1.7	2.1	2.0	2.4	2.7	1.7	2.1	2.0	2.4	2.7
	4H	1.6	2.0	2.0	2.3	2.6	1.6	2.0	2.0	2.3	2.6
	6H	1.6	1.9	1.9	2.3	2.6	1.6	1.9	1.9	2.2	2.6
	8H	1.5	1.9	1.9	2.2	2.5	1.5	1.9	1.9	2.2	2.5
	12H	1.5	1.8	1.9	2.2	2.5	1.5	1.8	1.9	2.2	2.5
4H	2H	1.6	2.0	2.0	2.3	2.6	1.6	2.0	2.0	2.3	2.6
	3H	1.5	1.8	1.9	2.2	2.5	1.5	1.8	1.9	2.2	2.5
	4H	1.4	1.7	1.8	2.1	2.5	1.4	1.7	1.8	2.1	2.5
	6H	1.3	1.6	1.7	2.0	2.4	1.3	1.6	1.7	2.0	2.4
	8H	1.3	1.5	1.7	1.9	2.4	1.3	1.5	1.7	1.9	2.4
	12H	1.2	1.4	1.7	1.9	2.3	1.2	1.4	1.7	1.9	2.3
8H	4H	1.3	1.5	1.7	1.9	2.4	1.3	1.5	1.7	1.9	2.4
	6H	1.2	1.4	1.6	1.8	2.3	1.2	1.4	1.6	1.8	2.3
	8H	1.1	1.3	1.6	1.8	2.3	1.1	1.3	1.6	1.8	2.3
	12H	1.1	1.2	1.6	1.7	2.2	1.1	1.2	1.6	1.7	2.2
12H	4H	1.2	1.4	1.7	1.9	2.3	1.2	1.4	1.7	1.9	2.3
	6H	1.1	1.3	1.6	1.8	2.3	1.1	1.3	1.6	1.8	2.3
	8H	1.1	1.2	1.6	1.7	2.2	1.1	1.2	1.6	1.7	2.2
Variations with the observer position at spacing:											
S =		1.0H	0.9 / -18.0				0.9 / -18.0				
		1.5H	9.7 / -18.3				9.7 / -18.3				
		2.0H	11.7 / -18.4				11.7 / -18.4				